CONTRACT DOCUMENT

2025 OPWC County Resurfacing Program

COSHOCTON COUNTY COMMISSIONERS 401½ Main Street Coshocton, OH 43812

> Coshocton County Engineer 23194 County Road 621 Coshocton, OH 43812

Bid Opening: Wednesday, April 16, 2025 at 10:00 a.m. Coshocton County Commissioners Office

Advertised: March 27, 2025; April 3, 2025 and online

COSHOCTON COUNTY ENGINEER 2025 OPWC COUNTY RESURFACING PROGRAM COSHOCTON COUNTY COMMISSIONERS

TABLE OF CONTENTS

DESCRIPTION	PAGE
BIDDING REQUIREMENTS	
Legal Notice - Invitation to Bid Information To Bidders Criteria for Selection of Competitive Bids	BR 1-4 BR 5-6
Wage Rates	2110
BIDDING FORMS	
Proposal Bond	BF 1-1A
Experience Statement	BF 2
Time Of Completion	BF 3
Certification Of Non-Segregated Facilities	BF 4
Form Of Non-Collusion Affidavit	BF 5
Personal Property Tax Affidavit	BF 6
Proposal Forms	BF 7-30
Bid Sheet	BF 31
CONTRACT FORMS	
Contract	CF 1
General Specifications	CF 2-3
Construction Regulations	CF 4-6
General Clauses	CF 7-16
Performance And Payment Bond	CF 17
Signature Sheet	CF 18
Legal And Fiscal Officers	CF 19

DETAILED SPECIFICATIONS

Asphalt Concrete Pavement Specifications

COSHOCTON COUNTY COMMISSIONERS COSHOCTON COUNTY ENGINEER 2025 OPWC COUNTY RESURFACING PROGRAM INVITATION TO BID

Sealed proposals for improvements by constructing the **2025 OPWC COUNTY RESURFACING PROGRAM**, Coshocton, Ohio, will be received by the Coshocton County Commissioners, Coshocton, Ohio at 401½ Main St., **10:00 a.m.**, **local time**, **Wednesday**, **April 16, 2025**, and then and there publicly opened and read. The work under this improvement consists of everything necessary to complete the project as shown by the plans and specifications for said items on file in the office of the County Engineer, 23194 County Road 621, Coshocton, Ohio 43812.

Complete specifications, including contract and proposal forms and full information for bidders may be obtained via the web at www.coshoctoncounty.net/engineer/current-bidding-projects/ or from the office of the County Engineer. Prospective bidders are required to register with Coshocton County in order to receive any addenda information.

Each proposal must be accompanied by a bond with an approved surety company as surety, in the sum of 100 percent of the amount of the bid as surety for the execution of the contract, or certified check for the amount of 10% of the bid on some solvent bank within the City of Coshocton, and made payable to the Coshocton County Treasurer, Coshocton, Ohio. Please mark all envelopes 2025 OPWC COUNTY RESURFACING PROGRAM, April 16, 2025.

The Owner reserves the right to waive any formalities or to reject any and all bids.

of County on Count	991011613	

ADVERTISED: March 27, 2025; April 3, 2025 and online

INFORMATION TO BIDDERS

All proposals must be made on the forms contained herein and the bid price must be written therein, in figures only. In all items, bids must be made separately on labor and material and the total price for each unit shall be the "Total (sum of labor and material)". In the event of conflict, the "Total" of the unit price or lump sum bid shall govern. Each bidder must bid on all items, alternates, deductions and additions contained in the bidding forms. All proposals not in conformity with this notice may be considered informal and may be rejected.

Potential bidders are required to register with the Office of the Coshocton County Engineer. Registration is complimentary and will ensure bidders receive any addendum and pertinent material. Each bidder is required to state in his proposal his name, place of residence and the names of all persons interested with him. In case of a corporation, the names of other than the president and secretary need not be given. References shall be furnished to establish the skill and business standing of the bidder.

The bidder must complete and submit all bidding forms as noted in the Table of Contents of these Contract Documents. Failure to complete the forms and submit the same at the bid opening may result in a non-responsive bid.

If any person contemplating submitting a bid for the proposed contract is in doubt as to the true meaning of any part of the plans, specifications, or other proposed contract documents, he may submit to the Engineer a written request for an interpretation thereof. The person submitting the request will be responsible for its prompt delivery. Any interpretation of the proposed documents will be made only by addendum duly issued and a copy of such addendum will be mailed or delivered electronically to each person receiving a set of such documents. The awarding authority will not be responsible for any other explanations or interpretations of the proposed documents. If there is a conflict between the detailed plans and specifications, the detailed plans shall prevail.

The bidder is required to examine carefully the site of the work, the proposal, plans and specifications, and to read and acquaint himself with the contract form for the work contemplated. The bidder, in submitting a proposal, warrants that he has investigated and is acquainted with the conditions to be encountered for performing the work including the character, quality and quantities of work to be performed and materials to be furnished, the prevailing hourly wage rates for the area in which the project is located and the requirements of the contract documents hereinafter defined. It is mutually agreed that submission of a proposal shall be considered prima facie evidence that the bidder has made such examination and is satisfied as to all conditions which will affect the work.

The quantities listed in the proposal form are to be considered as approximate and are to be used only for the comparison of the bids and as basis for computing amounts of security or penal sums of bonds to be furnished. The unit prices to be tendered by the bidders are to be tendered expressly for the scheduled quantities as they may be increased or decreased. Payments, except for lump sum contracts, will be made to the Contractor for the actual quantities only of work

performed or materials furnished in accordance with the plans and specifications, and it is understood that the scheduled quantities of work to be done and materials to be furnished may be increased or decreased without in any way invalidating the unit bid price.

The contractor shall submit a separate bill for quantities used on each road or street paved, unless otherwise directed. Daily quantities shall be provided based upon each roadway.

The successful bidder will be required to execute the contract within fifteen (15) days after the award of the work to him and shall furnish bond for the faithful performance of said contract in the sum of 100 percent of the total amount of his bid.

The contract bond shall be in the form attached to the specifications with an approved surety company as surety. In case of failure to execute the contract as stated or to furnish performance bond, the bidder will be considered to have abandoned the contract and the bond or check accompanying the proposal shall be forfeited to the Owner, not as penalty but as liquidated damages. The Coshocton County Commissioners must approve the sureties. The contract shall be awarded to the lowest and best bidder. Following the bid opening, the Owner shall determine the items, alternates and additions to be performed. Total bids will be calculated by adding the amounts bid by each bidder for such items, alternates and additions, less the deductions, so selected by the Owner in determining the lowest and best bid. The Owner reserves the right to reject any and all bids.

The successful bidder will be further required to furnish the Owner with a complete breakdown of the lump sum bid items, to the satisfaction of the Engineer, before signing the contract documents.

In determining the award, consideration will be given to (A) whether bidder maintains a permanent place of business, (B) suitability of the bidder's plant and equipment for the work, (C) bidder's financial status and organizations, (D) bidder's record of experience in constructing improvements of this type, (E) lowest and best bidder.

Check bid deposits of any bidders except the three lowest and best bidders will be returned within ten (10) days after opening bids. The bid deposit of the three lowest and best bidders will be returned within 48 hours after the executed contract and required bonds have been approved by the Owner.

The U.S. Department of Labor "Safety and Health Regulations for Construction" identified as Chapter XVII of Title 29, Code of Federal Regulations (CFR) Part 1926 (formerly Part 1518) and subsequent amendments are hereby made a part of these specifications.

Wherever the words "Owner" or "County" are used herein, they refer to the Coshocton County Commissioners, Ohio.

We are advised that materials to be incorporated in this work may be purchased by the Contractor free of State of Ohio sales tax.

Attention is called to the prevailing rates of wages to be paid for labor on public improvements in Coshocton County, Ohio, as ascertained by the Department of Industrial Relations, State of Ohio, or the Federal Department of Labor, as applicable.

The Owner reserves the right to hold bids for a period of sixty (60) days after date of opening and to award the contract at any time during that period.

Ohio Prevailing Wages SECTION 4115.071 (Wage Coordinator; powers and duties)

- (A) Each contracting public authority that enters into a contract other than for printing, binding and related services, whose Contractor and Subcontractors are subject to chapter 4115 of the Ohio Revised Code (ORC) shall, no later than ten days before the first payment of wages is payable to any employee of any Contractor or Subcontractor, designate and appoint one of its own employees to serve as the prevailing wage coordinator during the life of the contract. The duties of the coordinator shall include:
- 1. Setting up and maintaining, available for public inspection, files of payroll reports submitted by Contractors and Subcontractors pursuant to Chapter 4115 of the ORC;
- 2. Ascertaining from each Contractor or Subcontractor, at the beginning of performance under the contract, the dates during its life when payment of wages to employees are to be made;
- 3. Receiving from each Contractor or Subcontractor, a copy of his complete payroll for each date exhibiting for each employee paid any wages, his name, current address, social security number, number of hours worked each day during the pay period and the total for each week, his hourly rate of pay, his job classification, fringe payments, and deductions from his wages;
- 4. Establishing and following procedures to monitor the compliance by each Contractor and Subcontractor with the requirement imposed by this section for timely filing of copies of payroll records;
- 5. Reporting any delinquency in filing to the chief officer of the contracting public authority.
- (B) Any contracting public authority having a permanent employee with the title, powers and functions described herein for the prevailing wage coordinator need not separately designate and appoint an employee for each public work contract entered into by the contracting public authority.

2025 OPWC COUNTY RESURFACING PROGRAM COSHOCTON COUNTY BR 4

(C) Every Contractor and Subcontractor who is subject to Chapter 4115 of the ORC shall, as soon as he begins performance under his contract with any contracting public authority, supply to the prevailing wage coordinator of the contracting public authority a schedule of the dates during the life of his contract with the authority on which he is required to pay wages to employees. He shall also deliver to the prevailing wage coordinator a certified copy of his payroll, within three weeks after each pay date which shall exhibit for each employee paid any wages, his name, current address, social security number, number of hours worked during each day of the pay period and the total for each week, his hourly rate of pay, his job classification, fringe payments, and deductions from his wages. The certification of each payroll shall be executed by the Contractor, Subcontractor, or duly appointed agent thereof and shall recite that the payroll is correct and complete and that the wage rates shown are not less than those required by the contract.

Coshocton County Engineer 2025 OPWC County Resurfacing Program

Coshocton County Board of Commissioners' Criteria for Selection of Competitive Bids

GENERAL PROVISIONS

- 1. The contract will be awarded to the Contractor who submits the lowest and best bid for the project. Each Contractor shall submit evidence with their bid that they can comply with these specifications and that they are pre-qualified with the Ohio Department of Transportation for this work. The county reserves the right to add or delete from the estimated quantities. Factors to be considered by the Coshocton County Commissioners in determining which bid is the lowest and best will include:
 - A. each bidder's experience with similar projects and its ability to complete the work in a timely manner;
 - B. previous dealings between each bidder and the Coshocton County Board of Commissioners and/or the Project Manager;
 - C. each bidder's past history of initiating litigation and history of having litigation initiated against it;
 - D. any bidders' failure to fully respond to each question and/or to supply all information requested in the bid contract documents;
 - E. whether or not the bid guaranty documentation filed as required by R.C.§ 153.54 can be verified as authentic by the Coshocton County Commissioners;
 - F. each bidder's demonstration of its ability, at the time that the bid is awarded, to meet the specific requirements/scope of work of the Project Manager.
 - G. any recommendation of the Project Manager, although the Coshocton County Board of Commissioners retain the discretion to reject any recommendation of the Project Manager.
- 2. The Coshocton County Board of Commissioners reserve the right to waive any bid deficiency, so long as it is determined that the deficiency is minor and that the bidder does not receive a competitive advantage by this deficiency.
- 3. As required by R.C. § 153.54, each proposal must be accompanied by a certified check, bid bond or a letter of credit in an amount equal to 10% of total bid tendered, and made payable to Coshocton County Treasurer as a guarantee that, if the proposal is accepted, a contract will be retained upon proper execution of contract with successful bidder.
- 4. The successful bidder will be required to furnish a performance bond in the amount of 100% of his total bid, Certificate of Insurance, Workers Compensation certificate, an Affidavit for

2025 OPWC COUNTY RESURFACING PROGRAM COSHOCTON COUNTY BR 6

Contractor or Supplier of Non-Delinquency of Personal Property Taxes, and an Affidavit of Compliance of HB 694.

- 5. Traffic control will be provided by the Contractor in compliance with the OMUTCD. Traffic will be maintained through the project using flaggers or other approved traffic control devices. Maintenance of traffic shall be as provided in Item 614.
- 6. Work shall not commence prior to **August 4**, **2025** and shall be completed no later than **October 10**, **2025**.
- 7. The Coshocton County Board of Commissioners reserves the right to reject any and all bids.

Prevailing Wage Determination Cover Letter

County: COSHOCTON ✓

Determination Date: 03/19/2025 **Expiration Date:** 06/19/2025

THE FOLLOWING PAGES ARE PREVAILING RATES OF WAGES ON PUBLIC IMPROVEMENTS FAIRLY ESTIMATED TO BE MORE THAN THE AMOUNT IN O.R.C. SEC. 4115.03 (b) (1) or (2), AS APPLICABLE.

Section 4115.05 provides, in part: "Where contracts are not awarded or construction undertaken within ninety days from the date of the establishment of the prevailing wages, there shall be a redetermination of the prevailing rate of wages before the contract is awarded." The expiration date of this wage schedule is listed above for your convenience only. This wage determination is not intended as a blanket determination to be used for all projects during this period without prior approval of this Department.

Section 4115.04, Ohio Revised Code provides, in part: "Such schedule of wages shall be attached to and made a part of the specifications for the work, and shall be printed on the bidding blanks where the work is done by contract..."

The contract between the letting authority and the successful bidder shall contain a statement requiring that mechanics and laborers be paid a prevailing rate of wage as required in Section 4115.06, Ohio Revised Code.

The contractor or subcontractor is required to file with the contracting public authority upon completion of the project and prior to final payment therefore an affidavit stating that he has fully complied with Chapter 4115 of the Ohio Revised Code.

The wage rates contained in this schedule are the "Prevailing Wages" as defined by Section 4115.03, Ohio Revised Code (the basic hourly rates plus certain fringe benefits). These rates and fringes shall be a minimum to be paid under a contract regulated by Chapter 4115 of the Ohio Revised Code by contractors and subcontractors. The prevailing wage rates contained in this schedule include the effective dates and wage rates currently on file. In cases where future effective dates are not included in this schedule, modifications to the wage schedule will be furnished to the Prevailing Wage Coordinator appointed by the public authority as soon as prevailing wage rates increases are received by this office.

"There shall be posted in a prominent and accessible place on the site of work a legible statement of the Schedule of Wage Rates specified in the contract to the various classifications of laborers, workmen, and mechanics employed, said statement to remain posted during the life of such contract." Section 4115.07, Ohio Revised Code.

Apprentices will be permitted to work only under a bona fide apprenticeship program if such program exists and if such program is registered with the Ohio Apprenticeship Council.

Section 4115.071 provides that no later than ten days before the first payment of wages is due to any employee of any contractor or subcontractor working on a contract regulated by Chapter 4115, Ohio Revised Code, the contracting public authority shall appoint one of his own employees to act as the prevailing wage coordinator for said contract. The duties of the prevailing wage coordinator are outlined in Section 4115.071 of the Ohio Revised Code.

Section 4115.05 provides for an escalator in the prevailing wage rate. Each time a new rate is established, that rate is required to be paid on all ongoing public improvement projects.

A further requirement of Section 4115.05 of the Ohio Revised Code is: "On the occasion of the first pay date under a contract, the contractor shall furnish each employee not covered by a collective bargaining agreement or understanding between employers and bona fide organizations of Labor with individual written notification of the job classification to which the employee is assigned, the prevailing wage determined to be applicable to that classification, separated into the hourly rate of pay and the fringe payments, and the identity of the prevailing wage Coordinator appointed by the public authority. The contractor or subcontractor shall furnish the same notification to each affected employee every time the job classification of the employee is changed."

Work performed in connection with the installation of modular furniture may be subject to prevailing wage.

THIS PACKET IS NOT TO BE SEPARATED BUT IS TO REMAIN COMPLETE AS IT IS SUBMITTED TO YOU. (Reference guidelines and forms are included in this packet to be helpful in the compliance of the Prevailing Wage law.) wh1500

Prevailing Wage Rate Skilled Crafts

Name of Union: Truck Driver Locals 20,40,92,92b,100,175,284,438,377,637,908,957 - Bldg & HevHwy Class 1

Change #: LCN01-2024ibBldgHevHwy

Craft: Truck Driver Effective Date: 05/01/2024 Last Posted: 05/01/2024

	BI	HR		Fring	e Bene	fit Pay	ments		Irrevo Fur		Total PWR	Overtime Rate
			H&W	Pension	App Tr.	Vac.	Annuity	Other	LECET (*)	MISC (*)		
Clas	sificatio	n										
Truck Driver CLASS 1 4 wheel service, dump, and batch trucks; drivers on tandems; truck sweepers (not to include power sweepers & scrubbers)	\$31	1.84	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$49.84	\$65.76
Apprentice	Per	cent										
First 6 months	80.00	\$25.47	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$43.47	\$56.21
7-12 months	85.00	\$27.06	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$45.06	\$58.60
13-18 months	90.00	\$28.66	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$46.66	\$60.98
19-24 months	95.00	\$30.25	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$48.25	\$63.37

25-30	100.00 \$31	.84 \$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$49.84	\$65.76
months											

Special Calculation Note: No special calculations for this skilled craft wage rate are required at this time.

Ratio:

3 Journeymen to 1 Apprentice

Jurisdiction (* denotes special jurisdictional note) :

ADAMS, ALLEN, ASHLAND, ASHTABULA, ATHENS, AUGLAIZE, BELMONT, BROWN, BUTLER, CARROLL, CHAMPAIGN, CLARK, CLERMONT, CLINTON, COLUMBIANA, COSHOCTON, CRAWFORD, DARKE, DEFIANCE, DELAWARE, ERIE, FAIRFIELD, FAYETTE, FRANKLIN, FULTON, GALLIA, GREENE, GUERNSEY, HAMILTON, HANCOCK, HARDIN, HARRISON, HENRY, HIGHLAND, HOCKING, HOLMES, HURON, JACKSON, JEFFERSON, KNOX, LAWRENCE, LICKING, LOGAN, LORAIN, LUCAS, MADISON, MAHONING, MARION, MEDINA, MEIGS, MERCER, MIAMI, MONROE, MONTGOMERY, MORGAN, MORROW, MUSKINGUM, NOBLE, OTTAWA, PAULDING, PERRY, PICKAWAY, PIKE, PORTAGE, PREBLE, PUTNAM, RICHLAND, ROSS, SANDUSKY, SCIOTO, SENECA, SHELBY, STARK, SUMMIT, TRUMBULL, TUSCARAWAS, UNION, VAN WERT, VINTON, WARREN, WASHINGTON, WAYNE, WILLIAMS, WOOD, WYANDOT

Special Jurisdictional Note:

Details:

Prevailing Wage Rate Skilled Crafts

Name of Union: Truck Driver Locals 20,40,92,92b,100,175,284,438,377,637,908,957 - Bldg & HevHwy Class 2

Change #: LCN01-2024ibBldgHevHwy

Craft: Truck Driver Effective Date: 05/01/2024 Last Posted: 05/01/2024

	BI	łR		Fring	e Bene	fit Pay	ments		Irrevo Fur		Total PWR	Overtime Rate
			H&W	Pension	App Tr.	Vac.	Annuity	Other	LECET (*)	MISC (*)		
Classification												
Truck Driver CLASS 2	\$32	2.26	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$50.26	\$66.39
Tractor Trailer-Semi												
Tractor Trucks; Pole												
Trailers; Ready Mix												
Trucks; Fuel Trucks; 5												
Axle & Over; Belly												
Dumps; Low boys -												
Heavy duty												
Equipment(irrespective												
of load carried) when												
used exclusively for												
transportation; Truck												
Mechanics (when												
needed)												
Apprentice	Per	cent										
First 6 months	80.00	\$25.81	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$43.81	\$56.71
7-12 months	85.00	\$27.42	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$45.42	\$59.13
13-18 months	90.00	\$29.03	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$47.03	\$61.55
19-24 months	95.00	\$30.65	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$48.65	\$63.97
25-30 months	100.00	\$32.26	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$50.26	\$66.39

Special Calculation Note : No special calculations for this skilled craft wage rate are required at this time.

Ratio:

3 Journeymen to 1 Apprentice

Jurisdiction (* denotes special jurisdictional note):

ADAMS, ALLEN, ASHLAND, ASHTABULA, ATHENS, AUGLAIZE, BELMONT, BROWN, BUTLER, CARROLL, CHAMPAIGN, CLARK, CLERMONT, CLINTON, COLUMBIANA,

COSHOCTON, CRAWFORD, DARKE, DEFIANCE, DELAWARE, ERIE, FAIRFIELD, FAYETTE, FRANKLIN, FULTON, GALLIA, GREENE, GUERNSEY, HAMILTON, HANCOCK, HARDIN, HARRISON, HENRY, HIGHLAND, HOCKING, HOLMES, HURON, JACKSON, JEFFERSON, KNOX, LAWRENCE, LICKING, LOGAN, LORAIN, LUCAS, MADISON, MAHONING, MARION, MEDINA, MEIGS, MERCER, MIAMI, MONROE, MONTGOMERY, MORGAN, MORROW, MUSKINGUM, NOBLE, OTTAWA, PAULDING, PERRY, PICKAWAY, PIKE, PORTAGE, PREBLE, PUTNAM, RICHLAND, ROSS, SANDUSKY, SCIOTO, SENECA, SHELBY, STARK, SUMMIT, TRUMBULL, TUSCARAWAS, UNION, VAN WERT, VINTON, WARREN, WASHINGTON, WAYNE, WILLIAMS, WOOD, WYANDOT

Special Jurisdictional Note:

Details:

Prevailing Wage Rate Skilled Crafts

Name of Union: Truck Driver Locals 20,40,92,92b,100,175,284,438,377,637,908,957 - Bldg & HevHwy Class 3

Change #: LCN01-2024ibBldgHevHwy3

Craft: Truck Driver Effective Date: 05/01/2024 Last Posted: 05/01/2024

	BI	IR		Fring	e Bene	fit Pay	ments		Irrevo Fur		Total PWR	Overtime Rate
			H&W	Pension	App Tr.	Vac.	Annuity	Other	LECET (*)	MISC (*)		
Clas	sificatio	n										
Truck Driver CLASS 3 Articulated Dump Trucks; Ridge- Frame Rock Trucks; Distributor Trucks)	\$33	3.26	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$51.26	\$67.89
Apprentice	Per	cent										
First 6 months	80.00	\$26.61	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$44.61	\$57.91
7-12 months	85.00	\$28.27	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$46.27	\$60.41
13-18 months	90.00	\$29.93	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$47.93	\$62.90
19-24 months	94.96	\$31.58	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$49.58	\$65.38
25-30 months	100.00	\$33.26	\$8.00	\$9.60	\$0.40	\$0.00	\$0.00	\$0.00	\$0.00	\$0.00	\$51.26	\$67.89

Special Calculation Note : No special calculations for this skilled craft wage rate are required at this time.

Ratio:

3 Journeymen to 1 Apprentice

Jurisdiction (* denotes special jurisdictional note) :

ADAMS, ALLEN, ASHLAND, ASHTABULA, ATHENS, AUGLAIZE, BELMONT, BROWN, BUTLER, CARROLL, CHAMPAIGN, CLARK, CLERMONT, CLINTON, COLUMBIANA, COSHOCTON, CRAWFORD, DARKE, DEFIANCE, DELAWARE, ERIE, FAIRFIELD, FAYETTE, FRANKLIN, FULTON, GALLIA, GREENE, GUERNSEY, HAMILTON, HANCOCK, HARDIN, HARRISON, HENRY, HIGHLAND, HOCKING, HOLMES, HURON, JACKSON, JEFFERSON, KNOX, LAWRENCE, LICKING, LOGAN, LORAIN, LUCAS, MADISON, MAHONING, MARION, MEDINA, MEIGS, MERCER, MIAMI, MONROE, MONTGOMERY, MORGAN, MORROW, MUSKINGUM, NOBLE, OTTAWA, PAULDING, PERRY, PICKAWAY, PIKE, PORTAGE, PREBLE, PUTNAM, RICHLAND, ROSS, SANDUSKY, SCIOTO, SENECA, SHELBY, STARK, SUMMIT, TRUMBULL, TUSCARAWAS, UNION, VAN WERT, VINTON, WARREN, WASHINGTON, WAYNE, WILLIAMS, WOOD, WYANDOT

Special Jurisdictional Note:

Details:

Prevailing Wage Rate Skilled Crafts

Name of Union: Operating Engineers - HevHwy Zone II

Change #: LCN01-2024ibLoc18hevhwyll

Craft: Operating Engineer Effective Date: 06/05/2024 Last Posted:

06/05/2024

	BHR		Fring	e Bene	fit Pay	ments		Irrevo Fur		Total PWR	Overtime Rate
		H&W	Pension	App Tr.	Vac.	Annuity	Other	LECET (*)	MISC (*)		
Clas	sification										
Operator Class A	\$44.14	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$60.74	\$82.81
Operator Class B	\$44.02	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$60.62	\$82.63
Operator Class C	\$42.98	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$59.58	\$81.07
Operator Class D	\$41.80	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$58.40	\$79.30
Operator Class E	\$36.34	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$52.94	\$71.11
Master Mechanic	\$45.14	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$61.74	\$84.31
Crane and Mobile Concrete Pump 150' - 179'	\$44.64	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$61.24	\$83.56
Crane and Mobile Concrete Pump 180' - 249'	\$45.14	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$61.74	\$84.31
Crane and Mobile Concrete	\$45.39	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$61.99	\$84.69

Pump 250' and Over												
Apprentice	Per	cent										
1st Year	50.00	\$22.07	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$38.67	\$49.71
2nd Year	60.00	\$26.48	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$43.08	\$56.33
3rd Year	70.00	\$30.90	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$47.50	\$62.95
4th Year	80.00	\$35.31	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$51.91	\$69.57
Field Mech Trainee Class 2												
1st year	50.00	\$22.07	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$38.67	\$49.71
2nd year	60.00	\$26.48	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$43.08	\$56.33
3rd year	70.00	\$30.90	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$47.50	\$62.95
4th year	80.00	\$35.31	\$9.26	\$6.25	\$0.90	\$0.00	\$0.00	\$0.09	\$0.00	\$0.10	\$51.91	\$69.57

Special Calculation Note: Other: Education & Safety Fund

Misc: National Training

Ratio:

For every (3) Operating Engineer

Journeymen employed by the company, there AUGLAIZE, BELMONT, BROWN, may be employed (1) Registered Apprentice

or Trainee Engineer through the referral when they are available. An Apprentice, while employed as part of a crew per Article

VIII, paragraph 65 will not be subject to the apprenticeship ratios in this collective bargaining agreement

ADAMS, ALLEN, ASHLAND, ATHENS ADAMS, ALLEN, ASHLAND, ASHLAND

Jurisdiction (* denotes special jurisdictional note):

ADAMS, ALLEN, ASHLAND, ATHENS, CLARK, CLERMONT, CLINTON, COSHOCTON, CRAWFORD, DARKE, GALLIA, GREENE, GUERNSEY, HAMILTON, HANCOCK, HARDIN, HARRISON, HENRY, HIGHLAND, HOCKING, HOLMES, HURON, JACKSON, JEFFERSON, KNOX, LAWRENCE, LICKING, LOGAN, LUCAS, MADISON, MARION, MEIGS, MERCER, MIAMI, MONROE, MONTGOMERY, MORGAN, MORROW, MUSKINGUM, NOBLE, OTTAWA, PAULDING, PERRY, PICKAWAY, PIKE, PREBLE, PUTNAM, RICHLAND, ROSS, SANDUSKY, SCIOTO, SENECA, SHELBY, STARK, TUSCARAWAS, UNION, VAN WERT,

Special Jurisdictional Note:

Details:

**Apprentices wilt receive a 10% increase on top of the percentages listed above provided they are operating

mobile equipment. Mechanic Trainees will receive 10% increase if they are required to have CDL.

Class A - Air Compressors on Steel Erection; Asphalt Plant Engineers (Cleveland District Only); Barrier Moving Machine; Boiler Operators, Compressor Operators, or Generators, when mounted on a rig; Boom Trucks (all types); Cableways; Cherry Pickers; Combination- Concrete Mixers & Towers; Concrete Plants (over 4 yd capacity); Concrete Pumps; Cranes (all types); Compact Cranes track or rubber over 4,000 pounds capacity; Cranes self-erecting stationary, track or truck; Derricks (all types); Draglines; Dredges dipper, clam or suction; Elevating Graders or Euclid Loaders; Floating Equipment (all types); Gradalls; Helicopter Crew (Operator- hoist or winch); Hoes (all types); Hoisting Engines; Hoisting Engines, on shaft or tunnel work; Hydraulic Gantry (lifting system); Industrial-type Tractors; Jet Engine Dryer (D8 or D9) diesel Tractors; Locomotives (standard gauge); Maintenance Operators/Technicians (class A); Mixers, paving (single or double drum); Mucking Machines; Multiple Scrapers; Piledriving Machines (all types); Power Shovels, Prentice Loader; Quad 9 (double pusher); Rail Tamper (with automatic lifting and aligning device); Refrigerating Machines (freezer operation); Rotary Drills, on caisson work; Rough Terrain Fork Lift with winch/hoist; Side Booms; Slip Form Pavers; Survey Crew Party Chiefs; Tower Derricks; Tree Shredders; Trench Machines (over 24" wide); Truck Mounted Concrete Pumps; Tug Boats; Tunnel Machines and /or Mining Machines; Wheel Excavators.

Class B - Asphalt Pavers; Automatic Subgrade Machines, self-propelled (CMI-type); Bobcat-type and /or Skid Steer Loader with hoe attachment greater than 7000 lbs.; Boring Machine Operators (more than 48 inches); Bulldozers; Concrete Saws, Vermeer type; Endloaders; Horizontal Directional Drill (50,000 ft. lbs. thrust and over); Hydro Milling Machine; Kolman-type Loaders (production type-dirt); Lead Greasemen; Lighting and Traffic Signal Installation Equipment includes all groups or classifications; Maintenance Operators/Technicians, Class B; Material Transfer Equipment (shuttle buggy) Asphalt; Pettibone-Rail Equipment; Power Graders; Power Scrapers; Push Cats; Rotomills (all), Grinders and Planners of all types, Groovers (excluding walk-behinds); Trench Machines (24 inch wide and under).

Class C - A-Frames; Air Compressors, on tunnel work (low Pressure); Articulating/straight bed end dumps if assigned (minus \$4.00 per hour); Asphalt Plant Engineers (Portage and Summit Counties only); Bobcat-type and/or skid steer loader with or without attachments;

Drones; Highway Drills (all types); HydroVac/Excavator (when a second person is needed, the rate of pay will be "Class E"); Locomotives (narrow gauge); Material Hoist/Elevators; Mixers, concrete (more than one bag capacity); Mixers, one bag capacity (side loader); Power Boilers (over 15 lbs. pressure); Pump Operators (installing or operating well Points); Pumps (4 inch and over discharge); Railroad Tie Inserter/Remover; Rollers, Asphalt; Rotovator (lime-soil Stabilizer); Switch & Tie Tampers (without lifting and aligning device); Utilities Operators, (small equipment); Welding Machines and Generators.

Class D – Backfillers and Tampers; Ballast Re-locator; Bar and Joint Installing Machines; Batch Plant Operators; Boring Machine Operators (48 inch or less); Bull Floats; Burlap and Curing Machines; Concrete Plants (capacity 4 yds. and under); Concrete Saws (multiple); Conveyors (highway); Crushers; Deckhands; Farm type tractors, with attachments (highway); Finishing Machines; Firemen, Floating Equipment (all types); Fork Lifts (highway), except masonry; Form Trenchers; Hydro Hammers; Hydro Seeders; Pavement Breakers (hydraulic or cable); Plant Mixers; Post Drivers; Post Hole Diggers; Power Brush Burners; Power Form Handling Equipment; Road Widening Trenchers; Rollers (brick, grade, macadam); Self-Propelled Power Spreaders; Self-Propelled Sub-Graders; Steam Firemen; Survey Instrument men; Tractors, pulling sheepsfoot rollers or graders; Vibratory Compactors, with integral power.

Class E - Compressors (portable, Sewer, Heavy and Highway); Cranes-Compact, track or rubber under 4,000 pound capacity; Drum Firemen (asphalt plant); Fueling and greasing (Primary Operator with Specialized CDL Endorsement Add \$3.00/hr); Generators; Inboard-Outboard Motor Boat Launches; Masonry Fork Lifts; Oil Heaters (asphalt plant); Oilers/Helpers; Power Driven Heaters (oil fired); Power Scrubbers; Power Sweepers; Pumps (under 4 inch discharge); Signalperson; Survey Rodmen or Chairmen; Tire Repairmen; VAC/ALLS.

Master Mechanic - Master Mechanic

Cranes and Mobile Concrete Pumps 150' -179' - Boom & Jib 150 - 179 feet

Cranes and Mobile Concrete Pumps 180' - 249' - Boom & Jib 180 - 249 feet

Cranes and Mobile Concrete Pumps 250' and over - Boom & Jib 250 feet or over

Prevailing Wage Rate Skilled Crafts

Name of Union: Labor Local 134 Building

Change #: LCN01-2024ibLoc134

Craft: Laborer Effective Date: 05/01/2024 Last Posted: 05/01/2024

	BI	łR		Fring	e Bene	fit Pay	ments		Irrevo Fur		Total PWR	Overtime Rate
			H&W	Pension	App Tr.	Vac.	Annuity	Other	LECET (*)	MISC (*)		
Clas	sificatio	n										
Laborer Group A	\$31	.23	\$8.40	\$4.15	\$0.40	\$0.00	\$0.00	\$0.00	\$0.10	\$0.00	\$44.28	\$59.89
Laborer Group B	\$31	.63	\$8.40	\$4.15	\$0.40	\$0.00	\$0.00	\$0.00	\$0.10	\$0.00	\$44.68	\$60.50
Laborer Group C	\$32	2.16	\$8.40	\$4.15	\$0.40	\$0.00	\$0.00	\$0.00	\$0.10	\$0.00	\$45.21	\$61.29
Laborer Group D	\$32	2.58	\$8.40	\$4.15	\$0.40	\$0.00	\$0.00	\$0.00	\$0.10	\$0.00	\$45.63	\$61.92
Laborer Group E	\$21	.95	\$8.40	\$4.15	\$0.40	\$0.00	\$0.00	\$0.00	\$0.10	\$0.00	\$35.00	\$45.97
Apprentice	Per	cent										
0-1000 hrs	60.00	\$18.74	\$8.40	\$4.15	\$0.40	\$0.00	\$0.00	\$0.00	\$0.10	\$0.00	\$31.79	\$41.16
1001-2000 hrs	70.00	\$21.86	\$8.40	\$4.15	\$0.40	\$0.00	\$0.00	\$0.00	\$0.10	\$0.00	\$34.91	\$45.84
2001-3000 hrs	80.00	\$24.98	\$8.40	\$4.15	\$0.40	\$0.00	\$0.00	\$0.00	\$0.10	\$0.00	\$38.03	\$50.53
3001-4000 hrs	90.00	\$28.11	\$8.40	\$4.15	\$0.40	\$0.00	\$0.00	\$0.00	\$0.10	\$0.00	\$41.16	\$55.21
4001 - Plus	100.00	\$31.23	\$8.40	\$4.15	\$0.40	\$0.00	\$0.00	\$0.00	\$0.10	\$0.00	\$44.28	\$59.89

Special Calculation Note: \$0.10 for LECET is for Labor Management

Ratio : Jurisdiction (* denotes special jurisdictional note) :

- 1 Journeymen to 1 Apprentice
- 3 Journeymen to 1 Apprentice

Special Jurisdictional Note:

Details:

Group 1

Building and Construction Laborer, Signalman, Flagman, Tool Cribman, Carpenter Tenders, Finisher Tenders, Concrete Handler, Utility Construction Laborer, Guard Rail Erectors, Hazardous Waste Removal and Lead Abatement Level D Personal Protective Equipment (PPE)

Group 2

Bottom Men, Scaffold Builders, Tunnel Laborers, Pipe Layers, Air and Power Driven Tools, Burner on Demolition Work, Swinging Scaffold, Mucker, Caisson Worker, Cofferdam Worker, Powder Men and Dynamite Blasters, Creosote Workers, Form Setter, Plasterer Tender, Hod Carrier, Laser Beam Set-up Man, All Confined Space Work, Furnaces, Pickel Tubs, Acid Pits, and Hazardous Waste Removal and Lead Abatement Level C Personal Protective Equipment. (PPE)

Group 3

Mason Tender, Mortar Mixer, Stonemason Tender, Skid Steer Loader, Hazardous Waste Removal and Lead Abatement Level B Personal Protection Equipment (PPE)

Group 4

Laborers performing work pertaining to or in connection to repair of stoves, stacks, annealing process, soaking pits, coke batteries, boilers, power houses, chemical plants and ethanol plants (under National Maintenance Agreement) Gunnite Operator and Hazardous Waste Removal and Lead Abatement Level A Personal Protective Equipment (PPE)

Group 5

Watchman - Paid a weekly rate with overtime over forty (40) hours at time and one half (1-1/2) plus Health and Welfare, Pension, Training and Upgrading & LECET.

Prevailing Wage Rate Skilled Crafts

Name of Union: Labor HevHwy 3

Change #: LCN01-2024ibLocalHevHwy3

Craft: Laborer Group 1 Effective Date: 05/01/2024 Last Posted: 05/01/2024

	BI	łR		Fring	e Bene	fit Pay	ments		Irrevo Fur		Total PWR	Overtime Rate
			H&W	Pension	App Tr.	Vac.	Annuity	Other	LECET (*)	MISC (*)		
Clas	sificatio	n										
Laborer Group 1	\$35	5.52	\$8.40	\$4.15	\$0.45	\$0.00	\$1.50	\$0.00	\$0.10	\$0.00	\$50.12	\$67.88
Group 2	\$35	5.69	\$8.40	\$4.15	\$0.45	\$0.00	\$1.50	\$0.00	\$0.10	\$0.00	\$50.29	\$68.13
Group 3	\$36	5.02	\$8.40	\$4.15	\$0.45	\$0.00	\$1.50	\$0.00	\$0.10	\$0.00	\$50.62	\$68.63
Group 4	\$36	5.47	\$8.40	\$4.15	\$0.45	\$0.00	\$1.50	\$0.00	\$0.10	\$0.00	\$51.07	\$69.30
Watch Person	\$28	3.25	\$8.40	\$4.15	\$0.45	\$0.00	\$1.50	\$0.00	\$0.10	\$0.00	\$42.85	\$56.98
Apprentice	Per	cent										
0-1000 hrs	60.00	\$21.31	\$8.40	\$4.15	\$0.45	\$0.00	\$1.50	\$0.00	\$0.10	\$0.00	\$35.91	\$46.57
1001-2000 hrs	70.00	\$24.86	\$8.40	\$4.15	\$0.45	\$0.00	\$1.50	\$0.00	\$0.10	\$0.00	\$39.46	\$51.90
2001-3000 hrs	80.00	\$28.42	\$8.40	\$4.15	\$0.45	\$0.00	\$1.50	\$0.00	\$0.10	\$0.00	\$43.02	\$57.22
3001-4000 hrs	90.00	\$31.97	\$8.40	\$4.15	\$0.45	\$0.00	\$1.50	\$0.00	\$0.10	\$0.00	\$46.57	\$62.55
More than 4000 hrs	100.00	\$35.52	\$8.40	\$4.15	\$0.45	\$0.00	\$1.50	\$0.00	\$0.10	\$0.00	\$50.12	\$67.88

Special Calculation Note: Watchmen have no Apprentices. Tunnel Laborer rate with air-pressurized add \$1.00 to the above wage rate.

Ratio:

1 Journeymen to 1 Apprentice

3 Journeymen to 1 Apprentice thereafter

Jurisdiction (* denotes special jurisdictional note) :

ADAMS, ALLEN, ASHLAND, ATHENS, AUGLAIZE, BELMONT, BROWN,

BUTLER, CARROLL, CHAMPAIGN, CLARK, CLERMONT, CLINTON, COLUMBIANA, COSHOCTON, CRAWFORD, DARKE, DEFIANCE, DELAWARE, FAIRFIELD, FAYETTE, FRANKLIN, FULTON, GALLIA, GREENE, GUERNSEY, HAMILTON, HANCOCK, HARDIN, HARRISON, HENRY, HIGHLAND, HOCKING, HOLMES, JACKSON, JEFFERSON, KNOX, LAWRENCE, LICKING, LOGAN, MADISON, MARION, MEIGS, MERCER, MIAMI, MONROE, MONTGOMERY, MORGAN, MORROW, MUSKINGUM, NOBLE, PAULDING, PERRY, PICKAWAY, PIKE, PREBLE, PUTNAM, RICHLAND, ROSS, SCIOTO, SENECA, SHELBY, TUSCARAWAS, UNION, VAN WERT, VINTON, WARREN, WASHINGTON, WAYNE, WILLIAMS, WYANDOT

Special Jurisdictional Note : Hod Carriers and Common Laborers - Heavy, Highway, Sewer, Waterworks, Utility, Airport, Railroad, Industrial and Building Site, Sewer Plant, Waste Water Treatment Facilities Construction

Details:

Group 1

Laborer (Construction); Plant Laborer or Yardman, Right-of-way Laborer, Landscape Laborer, Highway Lighting Worker, Signalization Worker, (Swimming) Pool Construction Laborer, Utility Man, *Bridge Man, Handyman, Joint Setter, Flagperson, Carpenter Helper, Waterproofing Laborer, Slurry Seal, Seal Coating, Surface Treatment or Road Mix Laborer, Riprap Laborer & Grouter, Asphalt Laborer, Dump Man (batch trucks), Guardrail & Fence Installer, Mesh Handler & Placer, Concrete Curing Applicator, Scaffold Erector, Sign Installer, Hazardous Waste (level D), Diver Helper, Zone Person and Traffic Control.

*Bridge Man will perfomr work as per the October 31, 1949, memorandum on concrete forms, byand between the United Brotherhood of Caprpenters and Joiners of Americ and the Laborers' International Union of North America, which states in; "the moving, cleaning, oiling and carrying to the next point of erection, and the stripping of forms which are not to be re-used, and forms on all flat arch work shall be done by members of the Laborers' International Union of North America."

Asphalt Raker, Screwman or Paver, Concrete Puddler, Kettle Man (pipeline), All Machine-Driven Tools (Gas, Electric, Air), Mason Tender, Brick Paver, Mortar Mixer, Skid Steer, Sheeting & Shoring Person, Surface Grinder Person, Screedperson, Water Blast, Hand Held Wand, Power Buggy or Power Wheelbarrow, Paint Striper, Plastic fusing Machine Operator, Rodding Machine Operator, Pug Mill Operator, Operator of All Vacuum Devices Wet or Dry, Handling of all Pumps 4 inches and under (gas, air or electric), Diver, Form Setter, Bottom Person, Welder Helper (pipeline), Concrete Saw Person, Cutting with Burning Torch, Pipe Layer, Hand Spiker (railroad), Underground Person (working in sewer and waterline, cleaning, repairing and reconditioning). Tunnel Laborer (without air), Caisson, Cofferdam (below 25 feet deep), Air Track and Wagon Drill, Sandblaster Nozzle Person, Hazardous Waste (level B), ***Lead Abatement, Hazardous Waste (level C)

***Includes the erecting of structures for the removal, including the encapsulation and containment of Lead abatement process.

Group 3

Blast and Powder Person, Muckers will be defined as shovel men working directly with the miners, Wrencher (mechanical joints & utility pipeline), Yarner, Top Lander, Hazardous Waste (level A), Concrete Specialist, Curb Setter and Cutter, Grade Checker, Concrete Crew in Tunnels. Utility pipeline Tappers, Waterline, Caulker, Signal Person will receive the rate equal to the rate paid the Laborer classification for which the Laborer is signaling.

Group 4 Miner, Welder, Gunite Nozzle Person

A.) The Watchperson shall be responsible to patrol and maintain a safe traffic zone including but not limited to barrels, cones, signs, arrow boards, message boards etc. The responsibility of a watchperson is to see that the equipment, job and office trailer etc. are secure.

PROPOSAL BOND

as principal and as sureties, are hereby held and firmly bound unto the Coshocton County Commissioners, Ohio, as obligee in the penal sum of the dollar amount of the bid submitted by the principal to the obligee on, 2025, to undertake the project known as 2025 OPWC COUNTY RESURFACING PROGRAM, the penal sum referred to herein shall be the dollar amount of the principal's bid to the obligee, incorporating any additive or deductive alternate proposals made by the principal on the date referred to above to the obligee, which are accepted by the obligee. In no case shall the penal sum exceed the amount of \$\subseteq\$
For the payment of the penal sum well and truly to be made, we hereby jointly and severally bind ourselves, our heirs, executors, administrators, successors, and assigns.
Signed this day of, 2025.
THE CONDITION OF THE ABOVE OBLIGATION IS SUCH, that whereas the above named principal has submitted a bid for 2025 OPWC COUNTY RESURFACING PROGRAM fails to enter into a proper contract in accordance with the bid, plans, details, specifications, and bills of material; and in the event the principal pays to the obligee the difference not to exceed ten percent of the penalty hereof between the amount specified in the bid and such larger amount for which the obligee may in good faith contract with the next lowest bidder to perform the work covered by the bid or in the event the obligee does not award the contract to the next lowest bidder and resubmits the project for bidding, the principal pays to the obligee the difference not to exceed ten percent of the penalty hereof between the amount specified in the bid, or the costs, in connection with the resubmission, of printing new contract documents, required advertising, and printing and mailing notices to prospective bidders, whichever is less, than this obligation shall be null and void, otherwise to remain in full force and effect; if the obligee accepts the bid of the principal and the principal within ten days after the awarding of the contract enters into a proper contract in accordance with the bid, plans, details, specifications, and bills of material, which said contract is made a part of this bond the same as though set forth herein.
Now also, if the said shall well and faithfully do and perform the things agreed by the Coshocton County Commissioners to be done and performed according to the terms of said contract; and shall pay all lawful claims of Subcontractors, materialmen, and laborers, for labor performed and materials furnished in the carrying forward, performing, or completing of said contract; we agreeing and assenting that this undertaking shall be for the benefit of any materialman or laborer having a just claim, as well as for the obligee herein; then this obligation shall be void; otherwise the same shall remain in full force and effect; it being expressly understood and agreed that the liability of the surety for any and all claims hereunder

shall in no event exceed the penal amount of this obligation as herein stated.

2025 OPWC COUNTY RESURFACING PROGRAM COSHOCTON COUNTY BF 1A

That said surety hereby stipulates and agrees that no modifications, omissions, or additions, in or
to the terms of the said contract or in or to the plans or specifications therefor shall in any way
affect the obligations of said surety on its bond.

By:___ Surety

By:____ Principal

EXPERIENCE STATEMENT

5)

The Bidder is required to state in detail in the space provided below or separate submittal, what work he has done of a character similar to that included in the proposed Contract, to give references and such other detailed information as will enable the Owner to judge his responsibility, experience, skill and financial standing. Among other things, this statement shall include the following:

A record of similar work performed and evidence to the effect:

- 1) that the Bidder maintains a permanent place of business;
- 2) has adequate facilities and equipment available for the work under the proposed Contract;
- 3) that the Bidder has suitable financial means to meet obligations incidental to the work;
- 4) that the Bidder has appropriate technical experience and possesses sufficient skill and experience.

that the Bidder maintains a service department qualified to make all repairs or

adjustments that may be required on the equipment to be used under the proposed Contract.

TIME OF COMPLETION

The Bidder hereby certifies that he has examined the contract form and specifications for the project and is familiar with the liquidated damage features thereof and agrees to accomplish the specified work after August 4, 2025, and completed by October 10, 2025.

This period shall start from the day the Contractor receives his copy of the *Notice to Proceed*. The work covered by this completion guarantee shall include only those items listed for comparison of bids.

The prices for all items shall include the necessary labor, material, and equipment to complete the work as shown or specified.

The Bidder does hereby agree that in the event of failure on their part to contract as aforesaid (provided this proposal is accepted) the bond or certified check accompanying this proposal shall be forfeited to the Coshocton County Commissioners, Ohio, as liquidated damages.

The Bidder further agrees that the Owner may reject any or all bids.

Signed	Title
Company Name	
Address	

CERTIFICATION OF NON-SEGREGATED FACILITIES

The Bidder certifies that he does not maintain or provide for his employees any segregated facilities at any of his establishments, and that he does not permit his employees to perform their services at any location, under his control where segregated facilities are maintained. The Bidder certifies further that he will not maintain or provide for his employees any segregated facilities at any of his establishments, and that he will not permit his employees to perform their services at any location under his control where segregated facilities are maintained. The Bidder agrees that a breach of this certification will be a violation of the Equal Opportunity clause in any contract resulting from acceptance of this bid. As used in this certification, the term "segregated facilities" means any waiting rooms, work areas, restrooms and washrooms, restaurants and other eating areas, timeclocks, locker rooms, and other storage or dressing areas, parking lots, drinking fountains, recreation or entertainment areas, transportation, and housing facilities provided for employees which are segregated by explicit directive or are in fact segregated on the basis of race, color, religion, or national origin, because of habit, local custom, or otherwise. The Bidder agrees that (except where he has obtained identical certification from proposed Subcontractors for specific time periods) he will obtain identical certifications from proposed Subcontractors prior to the award of subcontracts exceeding \$10,000 which are not exempt from the provisions of the Equal Opportunity clause, and that he will retain such certifications in his files.

Note: The penalty for making false statements in offers is prescribed in 18 U.S.C. 1001.

FORM OF NON-COLLUSION AFFIDAVIT

STATE OF OHIO)
COUNTY OF) ss:)
Bid Identification: 2025 OPWC COUNTY R	ESURFACING PROGRAM Contractor's Official -
such bid is not made in the interest of or company, association, organization, or corposham: that said bidder has not directly or in in a false or sham bid, and has not directly or with any bidder or anyone else to put in a sthat said bidder has not in any manne communication or conference with anyone bidder, or to fix any overhead, profit, or cosbidder, or to secure any advantage against interested in the proposed contract. That a further, that said bidder has not, directly or in thereof, or the contents thereof, or divulged anot pay any fee in connection therewith, to organization, bid depository, or to any members.	the is sole Owner, a partner, president, secretary of, the party making the foregoing bid; that on behalf of any undisclosed person, partnership, oration; that such bid is genuine and not collusive or adirectly induced or solicited any other bidder to put indirectly colluded, conspired, connived, or agreed sham bid, or that anyone shall refrain from bidding; or, directly, or indirectly, sought by agreement, to fix the bid price to said bidder or of any other at element of such bid price, or of that of any other at the public body awarding the contract or anyone all statements contained in such bid are true; and, indirectly, submitted his bid price or any breakdown information or data relative thereto, or paid and will any corporation, partnership, company, association, per or agent thereof, or to any other individual except hip or other financial interest with said bidder in this
	Signed:
	Title
Subscribed and sworn to before me this	_day of, 2025.
	Notary
	My Commission Expires:

SEAL

2025 OPWC COUNTY RESURFACING PROGRAM COSHOCTON COUNTY BF 6

STATE OF OHIO) A FEIDAVIT
COUNTY OF	AFFIDAVIT)
	, being first duly sworn, deposes and says as
follows:	
1. He/she is the	of
which may receive a contract with the COUNTY RESURFACING PROGRAM,	Coshocton County Commissioners for 2023 OPWC
• 2 with any delinquent personal property to Coshocton County.	was not charged at the time the bid was submitted axes on the general tax list of personal property in
or	
• 2 with delinquent personal property taxes on County in the amount of \$ fo \$ for due and unpaid penaltic	n the general tax list of personal property in Coshocton or due and unpaid delinquent taxes and
charged with any delinquent personal prop transmit a copy of this statement to the Co	understands and agrees that, as required by ode, if this statement indicates that this Contractor is perty taxes, the Coshocton County Commissioners will ounty Treasurer, and that a copy of this statement will no payment shall be made with respect to any contract ated as a part thereof.
SWORN TO before me and subscribed in a	my presence this day of, 2025.
	Notary Public
	My Commission Expires:

• CROSS OUT THE PARAGRAPH 2 WHICH DOES NOT APPLY.

Coshocton County Engineer County

Road: CR 22

From: TR 341

To: CR 33

Length: 2.60 miles

Width: 21.0 feet

Courses: Scratch corrections at designated areas and 1.5" surface course

ESTIMATED QUANTITIES				
REF. NO.	ITEM	DESCRIPTION	QUANTITY	
1	254	Pavement Planing	53	sq. yards
2	407	Tack coat @ 0.05 gallon/SY	1602	gallons
6	449, type 1	1-½" surface course	2670	tons
7	407	Tack coat for corrections and drives	400	gallons
8	449, type 1	Surface course for corrections and drives	223	tons
11	617	RAP Berm	1017	tons
15	643	Centerline, 4"	2.6	miles
16	643	Edge Line, 4"	5.2	miles
18	614	Maintaining Traffic	1	LS

Coshocton County Engineer County

Road: CR 10

From: US 36

To: CR 425

Length: 3.00 miles

Width: 24.0 feet

Courses: Scratch corrections at designated areas and 1.5" surface course

ESTIMATED QUANTITIES				
REF. NO.	EF. NO. ITEM DESCRIPTION QUANTITY		ITITY	
1	254	Pavement Planing	53	sq. yards
2	407	Tack coat @ 0.05 gallon/SY	2112	gallons
6	449, type 1	1-½" surface course	3520	tons
7	407	Tack coat for corrections and drives	528	gallons
8	449, type 1	Surface course for corrections and drives	293	tons
11	617	RAP Berm	1173	tons
12	202	RPM Removals	324	each
15	643	Centerline, 4"	3	miles
16	643	Edge Line, 4"	6	miles
18	614	Maintaining Traffic	1	LS

Coshocton County Engineer County

Road: CR 621

From: Jackson St

To: US 36

Length: 0.41 miles

Width: 26.0 feet

Courses: 1" leveling and 1" surface

ESTIMATED QUANTITIES				
REF. NO.	ITEM	DESCRIPTION	QUANTITY	
1	254	Pavement Planing	65	sq. yards
2	407	Tack coat @ 0.05 gallon/SY	310	gallons
3	449, type 1	1" leveling course	345	tons
4	407	Tack coat @ 0.05 gallon/SY- intermed.	310	gallons
5	449, type 1	1" surface course	345	tons
7	407	Tack coat for corrections and drives	31	gallons
8	449, type 1	Surface course for corrections and drives	17	tons
11	617	RAP Berm	160	tons
13	621	Raised Pavement Markers	45	each
15	643	Centerline, 4"	0.41	miles
16	643	Edge Line, 4"	0.82	miles
18	614	Maintaining Traffic	lump	LS

Road: Bayberry Lane

From: Pleasant Valley Drive

To: Sleepy Hollow Drive

Length: 0.41 miles

Width: 32.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUAI	NTITY	
1	254	Pavement Planing	7733	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	390	gallons	
3	449, type 1	1" leveling course	430	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	390	gallons	
5	449, type 1	1" surface course	430	tons	
7	407	Tack coat for corrections and drives	39	gallons	
8	449, type 1	Surface course for corrections and drives	22	tons	
18	614	Maintaining Traffic	1	LS	

Road: Fulton Drive

From: Enslee Road

To: Forest Hill Drive

Length: 0.52 miles

Width: 28.0 feet

ESTIMATED QUANTITIES						
REF. NO.	ITEM	DESCRIPTION	QUA	NTITY		
1	254	Pavement Planing	8618	sq. yards		
2	407	Tack coat @ 0.05 gallon/SY	431	gallons		
3	449, type 1	1" leveling course	480	tons		
4	407	Tack coat @ 0.05 gallon/SY- intermed.	431	gallons		
5	449, type 1	1" surface course	480	tons		
7	407	Tack coat for corrections and drives	43	gallons		
8	449, type 1	Surface course for corrections and drives	24	tons		
9	604	Manholes, adj. to grade	4	each		
10	638	Valve Box, adj. to grade	5	each		
18	614	Maintaining Traffic	1	LS		

Road: S. 14th Street

From: East Main St

To: Spring St

Length: 0.34 miles

Width: 20.0 feet

ESTIMATED QUANTITIES						
REF. NO.	ITEM	DESCRIPTION	QUA	NTITY		
1	254	Pavement Planing	4027	sq. yards		
2	407	Tack coat @ 0.05 gallon/SY	201	gallons		
3	449, type 1	1" leveling course	224	tons		
4	407	Tack coat @ 0.05 gallon/SY- intermed.	201	gallons		
5	449, type 1	1" surface course	224	tons		
7	407	Tack coat for corrections and drives	20	gallons		
8	449, type 1	Surface course for corrections and drives	12	tons		
9	604	Manholes, adj. to grade	9	each		
10	638	Valve Box, adj. to grade	4	each		
14	644	12 foot Stop Bars	40	L.F.		
18	614	Maintaining Traffic	1	LS		

Road: 5th Street

From: Pine St

To: Main St

Length: 0.40 miles

Width: 24.0 feet

ESTIMATED QUANTITIES						
REF. NO.	ITEM	DESCRIPTION	QUANTITY			
1	254	Pavement Planing	5697	sq. yards		
4	407	Tack coat @ 0.05 gallon/SY- intermed.	229	gallons		
6	449, type 1	1-½" surface course	475	tons		
7	407	Tack coat for corrections and drives	23	gallons		
8	449, type 1	Surface course for corrections and drives	13	tons		
9	604	Manholes, adj. to grade	9	each		
10	638	Valve Box, adj. to grade	5	each		
14	644	12 foot Stop Bars	20	L.F.		
18	614	Maintaining Traffic		LS		

Road: 15th Street

From: Denman

To: South Dead End

Length: 0.20 miles

Width: 18.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUAI	NTITY	
1	254	Pavement Planing	2082	sq. yards	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	105	gallons	
6	449, type 1	1-½" surface course	174	tons	
7	407	Tack coat for corrections and drives	11	gallons	
8	449, type 1	Surface course for corrections and drives	6	tons	
9	604	Manholes, adj. to grade	1	each	
18	614	Maintaining Traffic	1	LS	

Road: 16th Street

From: Prospect St

To: Dehart Ave

Length: 0.11 miles

Width: 20.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUA	NTITY	
1	254	Pavement Planing	1311	sq. yards	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	66	gallons	
6	449, type 1	1-½" surface course	110	tons	
7	407	Tack coat for corrections and drives	7	gallons	
8	449, type 1	Surface course for corrections and drives	4	tons	
9	604	Manholes, adj. to grade	3	each	
18	614	Maintaining Traffic	1	LS	

Road: 19th Street

From: Hall Dr

To: Chestnut St

Length: 0.06 miles

Width: 20.0 feet

ESTIMATED QUANTITIES						
REF. NO.	ITEM	DESCRIPTION	QUAI	NTITY		
1	254	Pavement Planing	75	sq. yards		
4	407	Tack coat @ 0.05 gallon/SY- intermed.	94	gallons		
6	449, type 1	1-½" surface course	60	tons		
7	407	Tack coat for corrections and drives	9	gallons		
8	449, type 1	Surface course for corrections and drives	5	tons		
9	604	Manholes, adj. to grade	1	each		
18	614	Maintaining Traffic	1	LS		

Road: Beach Avenue

From: Cambridge Rd

To: Highland Blvd

Length: 0.22 miles

Width: 20.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUA	NTITY	
1	254	Pavement Planing	2633	sq. yards	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	132	gallons	
6	449, type 1	1-½" surface course	220	tons	
7	407	Tack coat for corrections and drives	14	gallons	
8	449, type 1	Surface course for corrections and drives	7	tons	
9	604	Manholes, adj. to grade	3	each	
10	638	Valve Box, adj. to grade	2	each	
18	614	Maintaining Traffic	1	LS	

Road: Hall Drive

From: 18th Street

To: Dead End

Length: 0.26 miles

Width: 20.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUAI	NTITY	
1	254	Pavement Planing	60	sq. yards	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	154	gallons	
6	449, type 1	1-½" surface course	257	tons	
7	407	Tack coat for corrections and drives	15	gallons	
8	449, type 1	Surface course for corrections and drives	9	tons	
9	604	Manholes, adj. to grade	3	each	
18	614	Maintaining Traffic	1	LS	

Road: Sara Drive

From: Cambridge Rd

To: Dead End

Length: 0.45 miles

Width: 23.0 feet

Courses: Var." Mill 5' from gutter edge, 1" Leveling and 1" Surface

ESTIMATED QUANTITIES						
REF. NO.	ITEM	DESCRIPTION	QUA	NTITY		
1	254	Pavement Planing	2611	sq. yards		
4	407	Tack coat @ 0.05 gallon/SY- intermed.	325	gallons		
6	449, type 1	1-½" surface course	542	tons		
7	407	Tack coat for corrections and drives	30	gallons		
8	449, type 1	Surface course for corrections and drives	17	tons		
14	644	12 foot Stop Bars	17	L.F.		
18	614	Maintaining Traffic	1	LS		

Road: Vine Street

From: 5th St

To: RR Tracks

Length: 0.54 miles

Width: 31.0 feet

ESTIMATED QUANTITIES						
REF. NO.	ITEM	DESCRIPTION	QUA	NTITY		
1	254	Pavement Planing	9782	sq. yards		
4	407	Tack coat @ 0.05 gallon/SY- intermed.	490	gallons		
6	449, type 1	1-½" surface course	816	tons		
7	407	Tack coat for corrections and drives	49	gallons		
8	449, type 1	Surface course for corrections and drives	27	tons		
9	604	Manholes, adj. to grade	11	each		
10	638	Valve Box, adj. to grade	2	each		
14	644	12 foot Stop Bars	90	L.F.		
18	614	Maintaining Traffic	1	LS		

Road: South Lawn Cemetery

From: All roads

To:

Length: 2.84 miles

Width: 17.0 feet

Courses: 1" leveling, 1" surface

ESTIMATED QUANTITIES						
REF. NO.	ITEM	DESCRIPTION	QUAN	ITITY		
2	407	Tack coat @ 0.05 gallon/SY	1415	gallons		
3	449, type 1	1" leveling course	1572	tons		
4	407	Tack coat @ 0.05 gallon/SY- intermed.	1415	gallons		
5	449, type 1	1" surface course	1572	tons		
18	614	Maintaining Traffic	1	LS		

Road: Walnut Street

From: 2nd St

To: Water St

Length: 0.08 miles

Width: 33.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUANTITY		
1	254	Pavement Planing	1642	sq. yards	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	82	gallons	
6	449, type 1	1-½" surface course	137	tons	
7	407	Tack coat for corrections and drives	8	gallons	
8	449, type 1	Surface course for corrections and drives	5	tons	
9	604	Manholes, adj. to grade	2	each	
14	644	12 foot Stop Bars	33	L.F.	
18	614	Maintaining Traffic	1	LS	

Road: Lavendar Lane

From: Morning Glory Rd

To: Johnson St

Length: 0.10 miles

Width: 27.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUA	NTITY	
1	254	Pavement Planing	1602	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	80	gallons	
3	449, type 1	1" leveling course	89	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	80	gallons	
5	449, type 1	1" surface course	89	tons	
7	407	Tack coat for corrections and drives	8	gallons	
8	449, type 1	Surface course for corrections and drives	5	tons	
18	614	Maintaining Traffic	lum	p LS	

Road: Morning Glory Rd

From: Dead End

To: Dead End

Length: 0.12 miles

Width: 27.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUAI	NTITY	
1	254	Pavement Planing	1893	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	95	gallons	
3	449, type 1	1" leveling course	106	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	95	gallons	
5	449, type 1	1" surface course	106	tons	
7	407	Tack coat for corrections and drives	10	gallons	
8	449, type 1	Surface course for corrections and drives	6	tons	
18	614	Maintaining Traffic	lum	p LS	

Road: N. Vine Street

From: W. Railroad St

To: W. Main St

Length: 0.04 miles

Width: 21.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUAI	NTITY	
1	254	Pavement Planing	495	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	25	gallons	
3	449, type 1	1" leveling course	28	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	25	gallons	
5	449, type 1	1" surface course	28	tons	
7	407	Tack coat for corrections and drives	3	gallons	
8	449, type 1	Surface course for corrections and drives	2	tons	
9	604	Manholes, adj. to grade	2	each	
14	644	12 foot Stop Bars	10.5	L.F.	
18	614	Maintaining Traffic	lumj	o LS	

Road: E Memco Street

From: N Kirk St

To: Dead End

Length: 0.03 miles

Width: 45.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUA	NTITY	
1	254	Pavement Planing	853	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	43	gallons	
3	449, type 1	1" leveling course	48	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	43	gallons	
5	449, type 1	1" surface course	48	tons	
7	407	Tack coat for corrections and drives	5	gallons	
8	449, type 1	Surface course for corrections and drives	3	tons	
18	614	Maintaining Traffic	lum	p LS	

Coshocton County Engineer Village of Warsaw

Road: Spring Mountain Road

From: Bridge St

To: Corp Limit

Length: 0.39 miles

Width: 24.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUAI	NTITY	
1	254	Pavement Planing	53	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	273	gallons	
3	449, type 1	1" leveling course	304	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	273	gallons	
5	449, type 1	1" surface course	304	tons	
7	407	Tack coat for corrections and drives	28	gallons	
8	449, type 1	Surface course for corrections and drives	15	tons	
18	614	Maintaining Traffic	1	LS	

Coshocton County Engineer Village of Nellie

Road: 3rd Street

From: Bridge St

To: Dead End

Length: 0.14 miles

Width: 21.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUAI	NTITY	
1	254	Pavement Planing	45	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	84	gallons	
3	449, type 1	1" leveling course	93	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	84	gallons	
5	449, type 1	1" surface course	93	tons	
7	407	Tack coat for corrections and drives	8	gallons	
8	449, type 1	Surface course for corrections and drives	5	tons	
18	614	Maintaining Traffic	1	LS	

Coshocton County Engineer Village of Nellie

Road: 1st Street

From: SR 79

To: 3rd St

Length: 0.15 miles

Width: 12.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUAN	ITITY	
1	254	Pavement Planing	45	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	51	gallons	
3	449, type 1	1" leveling course	57	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	51	gallons	
5	449, type 1	1" surface course	57	tons	
7	407	Tack coat for corrections and drives	5	gallons	
8	449, type 1	Surface course for corrections and drives	3	tons	
18	614	Maintaining Traffic	1	LS	

Coshocton County Engineer Franklin Twp

Road: TR 285

From: TR 479

To: CR 286

Length: 0.45 miles

Width: 20.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUAI	NTITY	
1	254	Pavement Planing	45	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	262	gallons	
3	449, type 1	1" leveling course	292	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	262	gallons	
5	449, type 1	1" surface course	292	tons	
7	407	Tack coat for corrections and drives	26	gallons	
8	449, type 1	Surface course for corrections and drives	15	tons	
11	617	RAP Berm	175	tons	
15	643	Centerline, 4"	0.45	miles	
16	643	Edge Line, 4"	0.9	miles	
18	614	Maintaining Traffic	1	LS	

Coshocton County Engineer Lafayette Twp

Road: TR 164

From: SR 541

To: 20100 Joint

Length: 0.63 miles

Width: 18.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUA	NTITY	
1	254	Pavement Planing	45	sq. yards	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	333	gallons	
6	449, type 1	1-½" surface course	555	tons	
7	407	Tack coat for corrections and drives	33	gallons	
8	449, type 1	Surface course for corrections and drives	19	tons	
11	617	RAP Berm	247	tons	
18	614	Maintaining Traffic	1	LS	

Coshocton County Engineer Tuscarawas Twp

Road: 6th St

From: Browns Lane

To: Corp Limit

Length: 0.27 miles

Width: 28.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUANTITY		
1	254	Pavement Planing	45	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	222	gallons	
3	448, type 1	1" leveling course	247	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	222	gallons	
5	448, type 1	1" surface course	247	tons	
7	407	Tack coat for corrections and drives	22	gallons	
8	448, type 1	Surface course for corrections and drives	12	tons	
11	617	RAP Berm	106	tons	
15	643	Centerline, 4"	0.27	miles	
16	643	Edge Line, 4"	0.54	miles	
17	643	Cross Walk	56	L.F.	
18	614	Maintaining Traffic	1	LS	

Coshocton County Engineer Tuscarawas Twp

Road: Squarewood St

From: 11th St

To: Clow Alley

Length: 0.13 miles

Width: 21.0 feet

ESTIMATED QUANTITIES					
REF. NO.	ITEM	DESCRIPTION	QUANTITY		
1	254	Pavement Planing	45	sq. yards	
2	407	Tack coat @ 0.05 gallon/SY	79	gallons	
3	448, type 1	1" leveling course	87	tons	
4	407	Tack coat @ 0.05 gallon/SY- intermed.	79	gallons	
5	448, type 1	1" surface course	87	tons	
7	407	Tack coat for corrections and drives	8	gallons	
8	448, type 1	Surface course for corrections and drives	4	tons	
18	614	Maintaining Traffic	lump	LS	

Coshocton County Engineer 2025 OPWC COUNTY RESURFACING PROGRAM

		APPROXIMATE			
REF. NO.	ITEM NO.	UNIT QUANTITIES	ITEM DESCRIPTION	UNIT PRICE	TOTAL PRICE
1	254	51,608 sq. yds	Pavement Planing		
7	407	7,675 gal.	Tack Coat @ 0.05 Gal./SY		
3	449, type 1	4,402 tons	1" Leveling Course		
7	407	5,971 gal.	Tack Coat @ 0.05 Gal/SY- Intermed.		
5	449, type 1	4,402 tons	1" Surface Course		
9	449, type 1	9,536 tons	1-½" surface course		
7	407	455 gal.	Tack coat for corrections and drives		
8	449, type 1	257 tons	Surface course for corrections and drives		
6	604	48 each	Manholes, Adj. to Grade		
10	8E9	18 each	Valve Box, Adj. to Grade		
11	617	2,878 tons	RAP berm		
12	202	324 each	RPM Removal		
13	621	45 each	RPM		
14	643	211 L.F.	Stop Bars		
15	643	6.73 miles	4" Center Line		
16	643	13.46 miles	4" Edge Lines		
17	643	56 L.F.	cross walk		
18	614	lump sum	Maintaining Traffic	Lump Sum	
19	254	51,608 sq. yds	Planing Grindings Hauled, As Per Plan		
			TOTAL		

	TOTAL AMOUNT OF BID IN WORDS	
COMPANY		
ADDRESS		
CITY	STATE	ZIP
SUBMITTED BY	TITLE	
COMPANY		
TELEPHONE	FAX	TAX ID NUMBER
EMAIL ADDRESS		

Acknowledgement of Published Addenda's:

CONTRACT

Coshocton County Commissioners, acting by	day ofby and between the and through its duly authorized agent hereinafter andof the City by of and State or", party of the second part.
promises and agreements on the part of the of and agreed and do hereby undertake, promise	presents, each in consideration of the undertakings, other herein contained, have undertaken, promised e and agree, the party of the first part for itself, its econd part for themselves and their heirs, executors, ows:
own cost and expense, furnish all the labor, respectively. The street of 2025 OPWC COUNTY RESURFACING thereto attached and the drawings therein ment information for bidders, general provisions, providing the street of the stre	aid party of the second part, shall and will at their materials, tools and equipment for the construction of PROGRAM , in accordance with specifications, attioned which specifications and drawings, with the roposal and bonds hereto attached which are hereby ork to be fully completed to the satisfaction of the
necessary to perform and complete in a	sary labor, materials, equipment, tools and services workmanlike manner all work required for the nee with the contract documents herein mentioned, including the following addenda:
ADDENDUM NO.	DATE

GENERAL SPECIFICATIONS

A.S.T.M. AND OTHER SPECIFICATIONS. Wherever in these specifications reference be made to the specifications of the American Society for Testing Material (abbreviated A.S.T.M. specifications) and to other similar specifications, codes, etc., such reference shall refer, unless otherwise denoted, to the latest effective specifications or codes indicated. All such specifications, codes, etc., referred to are hereby made a part of these specifications.

<u>CONTRACT DRAWINGS.</u> The locations and character of the work is shown on a set of drawings prepared by the County Engineer, Coshocton, Ohio.

<u>ORDER OF WORK.</u> The general order and sequence of construction of the work shall be subject to the approval of the Engineer. Before starting work, the Contractor shall submit a work schedule to the Engineer and receive approval of the same.

<u>SANITARY REGULATIONS</u>. Suitable sanitary conveniences for the use of all persons employed on the work, properly screened from public observation, shall be provided and maintained by the Contractor. The Contractor shall obey and enforce such other sanitary regulations and orders and shall take such precautions against infectious diseases as may be deemed necessary by the Engineer.

MAINTENANCE OF TRAFFIC AND FIRE PROTECTION. The Contractor shall at all times maintain free access to fire hydrants, water and gas valves and similar structures involving the public safety along the line of work. Clear way for traffic shall be provided at intersections, along the streets and wherever required by the Engineer to provide reasonable public safety measures.

Reasonable provision for pedestrian traffic shall be provided as directed.

<u>SPACE AVAILABLE FOR CONSTRUCTION OPERATIONS.</u> The Contractor shall confine his operations to the Owner's property and to property along right-of-way in accordance with the provisions of rights-of-way agreements which the Owner has obtained or may obtain for the work contemplated. Private property shall not be used by the Contractor without the Owner's consent upon submittal of work agreement between property owner and contractor.

SHEETING AND SHORING. It is the Contractor's responsibility to furnish, install and maintain sheeting, piling, shoring, and bracing, whether or not indicated on the drawings, to prevent earth movement which could damage the construction, or otherwise impair or delay the work or endanger human life. Remove the sheeting, shoring and bracing during backfilling unless otherwise noted on the drawings or directed in writing. Payment for such sheeting or piling shall be made under the respective Item. All sheeting or piling left in place shall be cut off at least two feet below final finish grade.

<u>WATERTIGHT STRUCTURES.</u> All structures to be used for holding water shall be made watertight and shall be tested by filling with water before they will be accepted. Tests of

concrete waterbearing basins shall be made before backfill is placed provided, however, that where special reasons make this impracticable, the Engineer may permit backfilling to proceed before test is made. Permission to make backfill shall not relieve the Contractor from any responsibility for watertightness of the structure and if upon making the tests the need to remove backfill arises it shall be done by and at the expense of the Contractor.

Structures required to withstand water pressure from outside shall also be tested as above where practicable.

<u>DISINFECTION.</u> Pipe lines, reservoirs, clear water basins and all structures designed to carry or hold water that is ready for domestic consumption shall be thoroughly cleaned and flushed and disinfected before being put in service and before acceptance by the Owner. Disinfection shall be done by the addition of suitable amounts of chlorine in the form of liquid chlorine or high test hypochloride of lime, the application to be made under the supervision of the Engineer. Tests for efficiency of disinfection may be made by the Owner and repeated disinfection shall be done by the Contractor when required.

APPROVAL OF MACHINERY AND EQUIPMENT. The Contractor shall submit to the Engineer for approval such detail drawings, sketches, specifications and descriptions as may be required to establish that each and every piece of machinery and/or equipment proposed by the Contractor for incorporation in the completed work fully conforms to the requirements of the plans and specifications as set forth herein. The approval of the Engineer of all machinery and/or equipment proposed for installation in the completed work shall be obtained by the Contractor before shipment of the same is made to the job. Prior to placing orders with manufacturers for equipment to be incorporated in the completed work, the Contractor shall submit to the Engineer for his preliminary approval as to type, data showing name of manufacturer, catalogue number or equivalent designation, and general description of the equipment offered.

These specifications and the plans prepared for the installation of this system are intended to be complete. Anything called for in the specifications and not shown on the plans must be furnished by the Contractor as though appearing in both plans and specifications.

<u>ODOT CONSTRUCTION AND MATERIALS SPECIFICATIONS.</u> The Standard Construction and Materials Specifications for the State of Ohio, Department of Transportation, 2023, including all changes and Supplemental Specifications referenced in this Bid Document shall govern this Contract.

CONSTRUCTION REGULATIONS

The following rules and regulations shall apply to all work to be done under this contract. If any provisions of these construction regulations conflict with any other clauses of this contract, the provision of these construction regulations shall take precedence.

- 1. <u>CONTRACT SECURITY</u>. The Contractor shall furnish a surety bond (form attached) in the amount at least equal to 100% of the contract price as security for the faithful performance of this contract and for the payment of all persons performing labor and furnishing materials in connection with this contract.
- 2. <u>CONTRACTOR'S INSURANCE</u>. The Contractor shall not commence work under this contract until he has obtained all insurance required under this paragraph and such insurance has been submitted and approved by the Owner, nor shall the Contractor allow any Subcontractor to commence work on his subcontract until all similar insurance required for coverage of the Subcontractor has been so obtained and approved.
- (A) <u>Compensation Insurance</u>. The Contractor shall take out and maintain during the life of this contract, worker's compensation insurance for all of his employees employed at the site of the project and, in case any work is sublet, the Contractor shall require the Subcontractor similarly to provide worker's compensation insurance for all of the latter's employees unless such employees are covered by the protection afforded by the Contractor.
- (B) <u>Contractor's Liability Insurance</u>. The Contractor agrees to maintain comprehensive general liability and automobile liability insurance covering all operations directly or indirectly incident to work under this contract whether such operations be by himself or by any Subcontractor or by anyone directly or indirectly employed by either of them. Such insurance coverage shall be maintained in the types and amounts herein specified for all work sublet, either by furnishing endorsements of his own liability insurance coverage or by requiring the Subcontractors concerned to furnish their own liability insurance of the types and in the amounts herein specified. Such comprehensive general liability insurance shall include coverage for:
- (1) Claims arising after the Contractor and Subcontractors have completed work (completed operations and products liability coverage), and
 - (2) Claims for property damage arising from excavation or tunneling operations, and
 - (3) Claims for property damage to any property below the surface of the ground, and
- (4) Claims arising from the liability assumed by the Contractor under this contract including third party beneficiary liability coverage.

When the work contemplated by the contract involves moving, shoring, underpinning, raising or demolition of any building or structures or involves blasting or the use of explosives the following coverage shall also be provided.

- (5) Claims for property damage arising from operations directly or indirectly incident to moving, shoring, underpinning, raising or demolition of any building or structure, and
- (6) Claims for property damage arising from operations directly or indirectly incident to blasting or explosions, however caused, and

The limits of liability of the insurance required herein shall be not less than \$500,000 each person and \$1,000,000 each occurrence for bodily injury and \$500,000 each occurrence for property damage. Umbrella excess liability insurance to extend existing policies to the limits shown will be accepted.

Such insurance policy(ies) as Contractor may carry to comply with this insurance requirement shall be endorsed to provide that the policy(ies) will not be changed or canceled without 30 days prior written notice to the Owner. Prior to the start of construction on each contract or subcontract, certificates of insurance establishing full compliance with these insurance requirements shall be submitted to the Owner. If any part of this contract is sublet, the Contractor is responsible for obtaining certificates of insurance establishing that the Subcontractors have complied with the insurance requirements herein contained. The Coshocton County Commissioners must be named as additional insured.

- 3. <u>WAGE RATES</u>. The wages to be paid for a legal day's work to laborers, workmen or mechanics engaged in work under this contract at the site of the project in the trade or occupation listed shall be not less than the wage rate set opposite the same, as predetermined by the Department of Industrial Relations of the State of Ohio, in accordance with Section 4115.04 of the Ohio Revised Code.
- 4. <u>POSTING MINIMUM WAGE RATES</u>. The Contractor shall post at conspicuous points on the site of the project a schedule showing all determined minimum wage rates and all authorized deductions, if any, from unpaid wages actually earned.
- 5. <u>ACCIDENT PREVENTION</u>. The Contractor shall be responsible for initiating, maintaining and supervising all safety precautions and programs in connection with the work. A copy of the Contractor's safety plan must be submitted with their bid.

The Contractor shall take all necessary precautions for the safety of, and shall provide all necessary protection to prevent damage, injury or loss to:

- (A) All employees on the work and all other persons who may be affected thereby.
- (B) All the work and all materials and equipment to be incorporated therein, whether in storage on or off the site, and

(C) Other property, at the site or adjacent thereto, including trees, shrubs, lawns, walk pavements, roadways, structures, and utilities not designated for removal, relocation or replacement in the course of construction.

The Contractor shall comply with all applicable laws, ordinances, rules, regulations and orders of any public authority having jurisdiction for the safety of persons or property or to protect them from damage, injury or loss. He shall erect and maintain, as required by existing conditions and progress of the work, all necessary safeguards for safety and protection, including posting danger signs, and other warnings against hazards, promulgating safety regulations and notifying Owners and users of adjacent utilities. Machinery, equipment, and all hazards shall be guarded or eliminated in accordance with accepted safety practices that are not in contravention of applicable law. When the use or storage of explosives or other hazardous materials or equipment is necessary for the execution of the work, the Contractor shall exercise the utmost care and shall perform such activities under the supervision of properly qualified personnel.

- 6. <u>CONSTRUCTION REPORTS.</u> The Contractor shall submit to the Owner schedules of costs and quantities of materials and other items, which schedules shall be in such form and shall be supported as to correctness by such of the estimates upon which they are based as the Owner may require. The Contractor shall also submit to the Owner the following records:
 - (A) Detailed estimate, and
 - (B) Periodical estimates for partial payment
- 7. PROGRESS REPORTS. The Contractor shall submit a progress schedule prior to the execution of the contract which will indicate the amount of work to be done each month during the life of the construction project. It is understood that this schedule may be changed during the course of the work as agreed between the Owner, Contractor and Engineer. The Contractor will, at least once a month, submit a schedule indicating the work accomplished to date. This information will be submitted in such a manner that it can be applied to the progress schedule previously submitted to indicate the relation between the work accomplished to any given date and the progress schedule originally established. Providing the work is behind schedule, the Contractor shall indicate the measure instigated to bring the job to schedule.

GENERAL CLAUSES

1. TIME OF COMMENCEMENT, RATE OF PROGRESS, AND TIME OF COMPLETION

The Contractor agrees that he will commence the work herein contracted to be done within ten days from the date of notice to that effect given in writing by the Owner; that the rate of progress of his work shall be such as, in the opinion of the Engineer, is necessary for completion within the time herein specified.

Subject to the applicable provisions of law, this contract shall be in full force and effect as a contract from and after the date when a fully executed and approved counterpart hereof is delivered to the Contractor.

The Owner has obtained or is in the process of obtaining the rights-of-way where necessary for the construction of the work under this contract. It shall be the responsibility of each bidder and Contractor to learn, prior to bidding, the status of acquisition of any rights-of-way necessary for the prosecution of the work and to keep informed on the progress made by the Owner in obtaining the rights-of-way during construction. In the event rights-of-way are not ready by the time the Contractor is ready to start work in any particular location, it is understood that the Contractor will not be entitled to any extra compensation because of the delay in carrying out the work. The Contractor will, however, be entitled to an extension of the specified time he is delayed as a result of the delay in obtaining the rights-of-way.

- 2. <u>WORKERS</u>. The Contractor shall at all times enforce strict discipline and good order among his employees and shall not employ on the work any unfit person or anyone not skilled in the work assigned to him. The Owner, or the Engineer shall have the authority to order the dismissal of any employee on the work who refuses or neglects to obey any of its instructions, or those of its inspectors relating to the carrying out of the provisions and intent of these specifications, or who is incompetent, unfaithful, abusive, threatening or disorderly in his conduct and such person shall not be again employed on the work.
- 3. <u>SUITABLE APPLIANCES TO BE USED.</u> The Contractor is to use such methods and appliances for the performance of all the operations connected with the work embraced under this contract as will insure satisfactory quality of work and a rate of progress which, in the opinion of the Engineer, will insure the completion of the work within the time herein specified. If, at any time before the commencement, or during the progress of the work, such methods or appliances appear to the Engineer to be inefficient or inappropriate for securing the quality of the work required or the said rate of progress, he may order the Contractor to increase their efficiency or improve their character, and the Contractor must conform to such order. But the failure of the Engineer to demand such increase of efficiency or improvement shall not relieve the Contractor from his obligations to secure the quality of work and the rate of progress established in these specifications.
- 4. <u>NO CLAIM FOR DAMAGES ON ACCOUNT OF DELAY.</u> The Contractor shall not be entitled to any claims for damages for any hindrance or delay from any cause whatever in the

progress of the work, or any portion thereof, but said hindrance may entitle said Contractor to such extension of time for completing the contract as may be determined by the Engineer; provided, he shall have given notice in writing of the cause of the delay within two weeks of said cause.

It is further understood and agreed that inclement weather shall not entitle the Contractor to any claim for damages.

- 5. <u>NO CLAIMS ON ACCOUNT OF UNFORESEEN DIFFICULTIES</u>. The Contractor agrees that he will sustain all losses or damages arising from the action of the elements, the nature of the work to be done under the specifications or from any unforeseen obstructions or encumbrances on the line of the work which may be encountered in the prosecution of the same.
- 6. <u>SUBSURFACE CONDITIONS</u>. It is the obligation and responsibility of the bidder to make his own investigations of subsurface conditions prior to submitting his proposal. The bidder may examine the records of all borings, test excavations and other subsurface investigations, if any, made solely for design purposes for the Owner. Said borings, test excavations, and other subsurface investigations, if any, are incomplete, are not a part of the contract document, except to the extent that the result thereof are specifically shown on the plans or included in the specifications, and are not warranted to show the actual subsurface conditions. The Contractor agrees that he will make no claim against the Owner or the Engineer, if, in carrying out the work, he finds that the actual subsurface conditions encountered do not conform to those indicated by said boring, test excavations and other subsurface investigations.
- 7. <u>UTILITIES AND STRUCTURES SHOWN ON THE PLANS.</u> The exact location and protection of utilities and structures is the responsibility of the Contractor. During construction, the Contractor shall use due diligence in protecting from damage all existing utilities and structures. If damage is caused, the Contractor shall be responsible for the repair or restoration of same to the satisfaction of the Engineer and for any resulting contingent damage.
- 8. PROTECTION OF FINISHED WORK. The Contractor will be held responsible for any and all materials or work to the full amount of payments made thereon, and will be required to make good, at his own cost, any injury or damage which said materials or work may sustain from any source or cause whatsoever, before final acceptance thereof. During freezing or severe winter weather, the Contractor shall provide the necessary drainage, heating facilities and other protection for the footers and floor slab to prevent any possible damage from frost action. It will also be necessary for the Contractor to provide protection to the walls from earth slippage and ponding of water and mud that could cause structural damage by freezing action.

- 9. PROTECTION OF PROPERTY AND LIVES. Said Contractor further agrees that he will indemnify, defend and save harmless said Owner and its officials, employees, agents and servants, including engineers and consultants employed under contract with the Owner to perform services on the projects covered by this contract, from all claims, suits, actions and proceedings of every name and description, which may be brought against said Owner, or its officials, employees, agents and servants, or said engineers and consultants, for or on account of any injuries or damages to persons or property received or sustained by any person or persons, firm or corporation, by or from said Contractor, or by or in consequence of any materials, or explosives used on said work, or by or on account of any improper material or workmanship in its construction, or by or on account of any accident, or of any other act or omission of said Contractor of his agents, or servants, and said Contractor also agrees that so much of the money due, or to become due, to him under this contract, as shall be considered necessary by said Owner may be retained by said Owner until such suits or claims for damages, or otherwise, as aforesaid, shall have been finally settled and determined and evidence to that effect finished to the satisfaction of said Owner.
- 10. <u>PROTECTION AGAINST CLAIMS FOR THE USE OF PATENTS.</u> All fees for any patented invention article or arrangements that may be used upon or in any manner connected with the construction, erection or maintenance of the work, or any part thereof, embraced in these specifications, shall be included in the price mentioned in the contract, and the Contractor shall protect and hold harmless the Owner against any and all demands for such fees or claims, and before the final payment or settlement is made on account of the contract, the Contractor shall furnish acceptable proof of a proper and satisfactory release from all such claims.
- 11. ASSIGNMENT OF THE CONTRACT AND SUBCONTRACTING. Said Contractor further agrees that he will not assign this contract or any part thereof or any of the money or orders payable under the contract without the previous written consent of said Owner and of Contractor's sureties endorsed on this contract but will keep the same under his personal control; that no right under this contract, nor to any moneys or orders due or to become due thereunder, shall be asserted against said Owner or any department, officer, or officers thereof, by reason of any so-called assignment, in law or equity, of this contract, or any part thereof, or of any moneys or orders payable thereunder unless such assignment shall have been authorized by the written consent of said Owner and Contractor's sureties endorsed on this contract; that no person other than said Contractor now has any claim thereunder, and that no claim shall be made excepting under this specific clause of this contract, and under that clause relating to claim or workmen and materialmen.
- 12. <u>CONTRACTOR NOT RELEASED BY SUBCONTRACTORS</u>. No subcontract shall under any circumstances relieve the Contractor of his liabilities and obligations under this contract; should any Subcontractor fail to perform the work undertaken by him in a satisfactory manner, and should this provision be violated, the Owner may, at his option, end and terminate such contract. The Subcontractor shall be governed by all requirements governing the general Contractor.

- 13. TERMINATION FOR BREACH. In the event that any of the provisions of this contract are violated by the Contractor or by any of his Subcontractors, the Owner may serve written notice upon the Contractor and the surety of its intention to terminate such contract, such notices to contain the reasons for such intention to terminate the contract and unless within 10 days after the serving of such notice upon the Contractor, such violation shall cease and satisfactory arrangement for correction be made, the contract shall, upon the expiration of said 10 days, cease and terminate. In the event of any such termination, the Owner shall immediately serve notice thereof upon the surety who shall have the right to take over and perform the contract, provided however that if the surety does not commence performance thereof within 30 days from the date of the mailing to such surety of notice of termination, the Owner may take over the work and prosecute the same to completion by contract for the account and at the expense of the Contractor, and the Contractor and his surety shall be liable to the Owner for any excess cost occasioned by the Owner hereby, and in such event the Owner may take possession of and utilize in completing the work, such materials, appliances, and plant as may be on the site of the work and necessary therefore.
- 14. <u>CLEANING UP AFTER THE COMPLETION.</u> When the work is completed, all pits, pipes, chambers, conduit, etc. shall be carefully cleaned out. The surrounding ground shall be cleared of all rubbish caused by construction; all sheds, etc., removed and the works left in a neat and presentable condition.
- 15. <u>REMOVAL OF CONDEMNED MATERIAL</u>. Defective work, materials, and equipment may be condemned by the Engineer at any time before the final acceptance of the work, and when such work has been condemned, it shall be immediately taken down by the Contractor and rebuilt in accordance with the plans and specifications. When defective material or equipment has been condemned, it shall be at once removed from the line of the work and stored as directed by the Engineer, or otherwise disposed of to his satisfaction. In case the Contractor shall neglect or refuse to remove or replace any rejected work, materials or equipment after a written notice, within the time designated by the Engineer, such work or material shall be removed or replaced by the Owner at the Contractor's expense.
- 16. <u>RELATIONS TO OTHER CONTRACTORS</u>. The Contractor is required, so far as possible, to so arrange his work and to dispose of his materials as will not interfere with the work or storage of materials of other Contractors engaged upon the work, if applicable. He is also required to join his work to that of others in a proper manner, and in accordance with the spirit of the plans and specifications, and to perform his work in the proper sequence in relation to that of other Contractors, and as may be directed by the Engineer.
- 17. CONTRACTOR TO KEEP SUPERINTENDENT AND ALSO COPY OF PLANS AND SPECIFICATIONS ON PROJECT. The Contractor shall keep on his work during its progress a competent superintendent and any necessary assistants, all satisfactory to the Engineer. The Superintendent shall represent the Contractor in his absence and all directions given to him shall be as binding as if given to the Contractor. Important instructions shall be confirmed upon written request in each case. The Superintendent shall keep all daily documentation on

production quantities and material types on an ongoing basis. The owner shall have access to this information at any time during the project. At all times when work is in progress, there shall be maintained on the site of the work, copies of plans and specifications, all in good order.

- 18. <u>FAULTS TO BE CORRECT AT ANY TIME BEFORE FINAL ACCEPTANCE</u>. Failure or neglect on the part of the Engineer or any of his authorized agents to condemn or reject bad or inferior work or materials, shall not be construed to imply an acceptance of such work or materials, if it becomes evident at any time prior to the final acceptance of the work and release of the Contractor by the Owner, neither shall it be construed as barring the Owner at any subsequent time from the recovery of damages or of such a sum of money as may be needed to build anew all portions of the work in which fraud was practiced or improper material hidden, whenever found.
- 19. <u>CONTRACTORS RESPONSIBILITY IN LAYOUT, LOCATION, INSPECTION AND TESTING.</u> The Contractor is also responsible for and shall check all leading dimensions and clearances as a whole and in detail, the fittings of all details, the exact proper position and elevation of all parts of the work and shall accomplish all field staking as may be necessary or required for construction. The Contractor must provide and maintain such facilities for the Engineer or his assistants as may be required for the convenient examination and inspection of the work in progress. The Contractor will pay the cost of testing all materials in laboratories or shops as he may be required by the contract to perform. The testing laboratory or shop shall be approved by the Engineer.
- 20. <u>AUTHORITY OF ENGINEER.</u> The Contractor agrees that the Engineer shall decide any and all questions of fact which may arise under this contract, including the quantity, quality or acceptability of materials and equipment furnished and work performed and rate of progress of the work, whether or not such questions involve the interpretation of the plans and specifications. The Engineer shall have the right to correct any errors or omissions therein, when such corrections are necessary to the proper fulfillment of the intention of said plans and specifications. The Engineer's decision regarding any question governed by this provision shall be final and conclusive.
- 21. <u>DISPUTES</u>. Except as otherwise provided herein, any dispute arising under this contract shall be settled, if possible, by negotiation and mutual agreement of the parties hereto. In the event of their inability to agree, the Engineer shall reduce his findings to writing and mail or otherwise furnish a copy thereof to the Contractor. Within 10 days from the date of receipt of such copy, the Contractor may appeal by mailing or otherwise furnishing to the Owner, a written request to submit the dispute to the arbitration of two persons, one to be appointed by each party to this agreement. If the two persons so appointed are unable to agree within a period of 10 days, then such two arbitrators shall appoint a third arbitrator. Thereafter, the three arbitrators shall decide the arbitration as soon as possible. An award, in writing, signed either by the first two arbitrators appointed, or by two of the three arbitrators, if there are three, shall be final and conclusive as to both parties hereto. Neither party hereto shall have recourse to any court of law or equity as to any disagreement or difference which is subject to arbitration under this clause, except in the event the award of the arbitrators shall call for an expenditure by either party of an amount in excess of \$2,000.00 or one percent of the original

contract award price (amount of the contract), whichever is greater, or except for the purpose of confirmation, vacating, or modifying, or correcting the award of the arbitrators, on the grounds, for the causes and under the provisions of the Ohio Arbitration Act, R.C. 2711.01 et. seq. If no such appeal to arbitration is taken, the decision of the Owner's engineer shall be final and conclusive. Pending final decision of a dispute hereunder, the Contractor shall proceed diligently with the performance of the contract and in accordance with the Engineer's decision.

22. CHANGES AND EXTRA WORK.

INCREASED OR DECREASED QUANTITIES. The Owner may make alterations in the plans involving increases or decreases in the quantity of work as may be necessary or desirable to complete the project within the scope of the work. Such alterations shall not be considered as a waiver of any of the conditions of the contract, nor invalidate any of the provisions thereof.

EXTRA WORK. Extra work is authorized new work made necessary by alteration of the plans or found necessary by the Engineer during construction and is limited to work other than that required to complete the improvement as detailed on the plans or specified in the specifications. Extra work shall be performed by the Contractor in accordance with the specifications where applicable and work not covered by the specifications shall be done in accordance with the best practice as approved by the Engineer provided, however, that before any extra work is started a written change order, from the Owner, shall be delivered to the Contractor to do the work. When the nature of the extra work required is such that the exact amount of work to be done cannot be determined precisely, the Contractor shall proceed only as directed by the Owner.

PAYMENT AND COMPENSATION FOR ALTERED QUANTITIES OF EXTRA WORK. When the Owner orders alterations in the plans or quantities of work for which unit prices are provided in the proposal, the Contractor shall accept payment in full at the contract unit prices bid for the actual quantities of work done and no allowance will be made for any increased expense, loss of expected reimbursement, or loss of anticipated profits suffered or claimed by the Contractor resulting either directly from such alterations, or indirectly from unbalanced allocation among the contract items of overhead expense on the part of the bidder and subsequent loss of expected reimbursement therefore, or for any other cause.

Authorized alterations in plans or quantities of work involving work not covered by unit prices in the proposal shall be paid for as stipulated in the change order authorizing such work. The value of the work not covered by the contract unit bid prices shall be determined in one or more of the following ways:

- (A) By estimate and agreement in a lump sum.
- (B) By unit prices agreed upon.
- (C) By actual cost plus an agreed percentage.

The Contractor shall furnish substantiating data required in the preparation of all change orders for extra work items involving lump sum or new unit prices.

In the event an agreement as to the value of the work cannot be reached, the Owner reserves the right to have such extra work done by any other person, firm or corporation and that said Contractor further agrees that he will not, in any way, interfere with or molest such person, firm or corporation in the execution of the work.

EXTENSION OF TIME. Alterations or extra work authorized as provided herein-before which results in delays beyond the control of the Contractor or which materially increases the scope or intent of the project, shall entitle the Contractor to such extension of time as may be mutually agreed upon.

23. <u>DEFINITIONS</u>. Whenever the word "Engineer" is used herein, it shall be and is mutually understood to refer to the County Engineer.

Whenever the word "Owner" is used herein, it shall be understood to refer to the Coshocton County Commissioners.

- 24. <u>THE CONTRACT</u>. It is mutually understood that the contract is the written agreement covering the performance of the work and the furnishing of labor and materials in the construction of the work. The contract includes the advertisement, the information to bidder, the proposal, all drawings, maps and plans hereto attached or herein described, the specifications, the contract bond, and any and all extra work contracts or other supplemental agreements.
- 25. <u>DAMAGES BY FAILURE TO COMPLETE THE WORK WITHIN THE TIME AGREED UPON, OR AS EXTENDED.</u> The Contractor hereby agrees that the said Owner shall be and are hereby authorized to deduct and retain out of the moneys which may be due or become due to the said Contractor, under this agreement, as damages for the non-completion of the work aforesaid within the time hereinbefore stipulated for its completion or within such further time as in accordance with the provision of this agreement shall be fixed or allowed for such performances or completion, the sum of \$300 per day for contract amounts from \$0 to \$200,000, and \$600 per day for all contracts over \$200,000 for each and every day the time employed upon said work may exceed the time stipulated for its completion, or such stipulated time as the same may be increased, as hereinbefore provided, which said sum of \$300 per day for contract amounts from \$0 to \$200,000 and \$600 per day for all contracts over \$200,000 is hereby, in view of the difficulty of estimating such damages, agreed upon, fixed and determined by the parties hereto as the liquidated damages that the Owner will suffer by reason of such default and not by way of penalty.
- 26. OWNER'S RIGHT TO WITHHOLD CERTAIN AMOUNTS. Upon non-payment by the Contractor for a period of ten (10) days after due date of just claim for labor done under this contract or upon non-payment by the Contractor for a period of thirty (30) days after due date of just claims for material furnished under this contract, the Owner may retain from subsequent

estimate due the Contractor such amount as the Owner deems necessary in order to pay such just overdue claims.

- 27. <u>PROVISIONS OF LAW.</u> Each and every provision of law and clause required by law to be inserted in this contract shall be deemed to be inserted herein and this contract shall be read and enforced as though it were included herein and if through mere mistakes or otherwise any such provision is not inserted, or is not correctly inserted, then upon the application of either party hereto, the contract shall forthwith be physically amended to make such insertion.
- 28. QUALITY OF MATERIALS. Wherever in the contract documents a particular brand, make of material, device or equipment is shown or specified, such brand, make of materials, device or equipment is to be regarded merely as a standard meeting specifications and such trade name shall be considered to be followed by the clause "or equal". If two or more brands, makes of material, devices or equipment are shown or specified, each is to be regarded as the equal by the Owner. Any other brand, make of material, device or equipment which, in the opinion of the Engineer, is recognized equal of that specified, considering quality workmanship, economy of maintenance and operation, availability of repair work, duration of life, and is suitable for the purpose intended will be accepted. In those instances in which a particular brand, make of material, device or equipment is required to be stated by the Contractor in the bidding form, Contractor is required to provide the item so indicated unless otherwise approved by the Engineer by written change order. All material and workmanship shall in every respect be in accordance with what, in the opinion of said Engineer, is the best modern practice, and wherever the plan, drawings, specifications or other contract documents, or the directions of the Engineer admit doubt as to what is permissible and/or fail to note the quality of any work, that interpretation which requires the best quality of materials and workmanship in conformity with the best modern practice is to be followed.
- 29. <u>ADEQUATE SURETIES.</u> If, at any time after execution and approval of this contract and the performance bond required by the contract documents, the Owner shall deem any of the sureties upon such bond to be unsatisfactory, or if, for any reason, such bond shall cease to be adequate security for the Owner, the Contractor shall, within five days after notice of the Owner so to do, furnish a new or additional bond, in form, sum and signed by such sureties as shall be satisfactory to the Owner. No further payment shall be deemed due nor shall any further payment be made to the Contractor unless and until such new or additional bond shall be furnished and approved. The premium on such bonds shall be paid by the Contractor.
- 30. <u>NOTICES</u>. Notice shall mean written notice. Written notice shall be deemed to have been duly served when delivered in person to the person, firm, or corporation for whom intended, or to his or its duly authorized officer, agent or representative, or when delivered at the last known business address of such person, firm or corporation, or when enclosed in a postage prepaid wrapper or envelope addressed to such person, firm or corporation at his, their or its last known business address and sent by registered mail with return receipt requested.

31. MONTHLY ESTIMATES. On the first of each month, or within seven days thereof, during construction, the Contractor shall prepare and submit to the Engineer for approval, an estimate of the amount of labor performed and of the amount of materials incorporated in the work and/or acceptable materials delivered to the site.

Partial payment to the Contractor for work performed under a lump sum price shall be based on the detailed breakdown of the bid showing labor and material as prepared by the Contractor preceding start of construction and approved by the Engineer.

An Act of the 103rd General Assembly of the State of Ohio (Am. Sub. House Bill No. 627) is interpreted as follows:

Acceptable materials delivered to the site but not incorporated in the work will be paid at 92% of the invoice value of same. Until the job is 50% completed, the Contractor will be paid 92% of the estimated value of labor and material completed in acceptable form. This 8% retention of the first 50% of the job will be held by the Owner until 30 days after completion. After the job is 50% completed, material incorporated in the work and labor will be paid for at 100% of the estimated value of same as bid.

When the work is completed to the satisfaction of the Engineer and the Owner, the Contractor shall be paid an amount which will bring the total payments to him up to 96% of the contract price.

Estimates and payments shall be made about the first of each month unless, as provided by the act, when the rate of work and mounts involved are so large that it is deemed advisable by the Owner or Contractor, estimates and payments shall be made twice each month.

The Act makes reference to payments of estimates unless the Contractor does not prosecute the work with diligence and with the force specified or intended in the contract.

From the date of satisfactory completion and acceptance of the work, 4% shall be retained as additional security for thirty days for the faithful performance of the contract, after which time, if the contract has been faithfully performed, nothing shall be retained.

32. <u>REPAIRS FOR ONE YEAR.</u> The Contractor shall make all repairs due to defective workmanship or materials for the term of one year after the final acceptance date and shall correct and repair promptly during that time all defective work and material or whatever description. However, ordinary wear and tear or damage due to negligent or improper operation or maintenance on the part of the Owner shall not be considered any obligation of the Contractor. In case the Contractor shall neglect or fail to promptly make said repairs, after written notification, the Owner shall cause such repairs to be made at the expense of the Contractor and/or his surety.

As a guarantee for the faithful performance of the repairs for one year as outlined above, the Contractor shall furnish to the Owner a surety bond executed by an acceptable surety company in an amount of five percent of the final contract amount.

- 33. <u>NON-DISCRIMINATION IN EMPLOYMENT</u>. The Contractor agrees that in the hiring of employees for the performance of work under this contract or any subcontract, neither the Contractor, nor any Subcontractor, nor any person acting on behalf of either, shall, by reason of race, creed, or color, discriminate against any citizen of the State in the employment of labor or workers who are qualified and available to perform the work to which the employment relates; nor shall the Contractor, or any Subcontractor, or any person acting on behalf of either, in any manner discriminate against or intermediate any employee hired for the performance of work under this contract on account of race, creed or color.
- 34. The Contractor is hereby notified that city income tax must be deducted from all employees for any portion of this project which may be subject to municipal income tax and said Contractor must abide by all rules of the applicable municipal income tax department.
- 35. <u>ASSIGNMENT</u>. The Contractor shall not, without the written consent of the Owner, assign, transfer, convey, subcontract or otherwise dispose of or encumber this Contract or any part of his interest herein or in any of the moneys due or to become due and payable hereunder.

Funds payable to an assignee under any approved assignment shall be subject to all set-offs to which the Owner is otherwise entitled and to prior liens for services rendered and materials supplied in favor of all persons, firms or corporations rendering such services or supplying such materials.

In making application for subcontracting any portion of this contract, the Contractor shall state in writing to the Owner what such other information as may be required by the Owner, in order to ascertain whether such Subcontractor is responsible and able to perform the work or to furnish the materials as called for in the contract documents. The Owner will consider the Contractor's application to subcontract work and advise him by letter of its decision within seven days thereof. Subcontractors shall be bound to all of the conditions and covenants of the contract, except as may otherwise be agreed by the Owner in granting approval for their use.

The Contractor shall not subcontract more than 49% of the General Contract.

36. <u>RESPONSIBILITY OF THE CONTRACTOR</u>: The Contractor shall take all responsibility for work performed by them on the project, shall bear all losses resulting to them on account of the amount or character of the work or from any unforeseen obstruction or difficulties which may be encountered, or because the nature of the land in or on which the work is done is different from that which is assumed or was expected, or on account of the weather, floods, or other causes; and the Contractor shall assume the defense of and shall indemnify and save harmless the Coshocton County Commissioners, its officers and agents from all claims of any kind arising from the performance of their work on the project.

PERFORMANCE AND PAYMENT BOND

"KNOW ALL MEN BY THESE PRESENT,	that we, the undersigned as ties, are hereby and firmly bound unto the
Coshocton County Commissioners, Ohio, in t	he penal sum of \$ to perform the
project known as 2025 OPWC COUNTY I	RESURFACING PROGRAM, for the payment of
	by jointly and severally bind ourselves, our heirs,
executors, administrators, successors, and ass	igns.
Signed this day of,	2025.
THE CONDITION OF THE ABOVE OBLI	GATION IS SUCH, that whereas the above named
principal did on theday of	, 2025, enter into a contract with the Coshocton
County Commissioners, Ohio, to underta	ke the project known 2025 OPWC COUNTY
	contract is made a part of this bond the same as
though set forth herein;	
Now, if the said shall w	ell and faithfully do and perform the things agreed
by the Coshocton County Commissioners, Ol	ell and faithfully do and perform the things agreed hio, to be done and performed according to the said
contract; and shall pay all lawful claims of S	subcontractors, materialmen, and laborers, for labor
	rrying forward, performing, or completing of said
	this undertaking shall be for the benefit of any
<u> </u>	s well as for the obligee herein; then this obligation main in full force and effect; it being expressly
	e surety for any and all claims hereunder shall in no
event exceed the penal amount of this obligat	
• •	modifications, omissions, or additions, in or to the as or specifications therefor shall in any wise affect
·	
Principal	Surety
1	
Address	Address

SIGNATURE SHEET

Coshocton County Co.	mmissioner	5
Date:		
Signed		Title
Contractor's Name		
Federal I.D. No		
Address		
G'	- Ct. t	7.
City	State	Zip
Teleph	one No.	
Date:		
	Coshocton County Coshocton	Contractor's Name Federal I.D. No. Address City State Telephone No.

LEGAL AND FISCAL OFFICERS

	, 2025
The foregoing contract is approved	as to form.
	Benjamin E. Hall Coshocton County Prosecutor
	Control County 1100000101
acting fiscal officer of Coshocton Crequired to meet the cost of the atta Ohio, Owner, and Ohio Public Works Grant identificand Local Motor Vehicle Gas Partial Villages has been lawfully appropriated fund for	ounty Auditor, do hereby certify that I am the qualified and County, Ohio, and the amount of money to wit \$
	,2025
	Grant Daugherty Coshocton County Auditor

ASPHALT CONCRETE PAVEMENT SPECIFICATIONS 2025 OPWC COUNTY RESURFACING PROGRAM

LOCATION: The work proposed under this contract is located in Coshocton County and various locations in the county and townships of Coshocton County as specified.

THIS PROJECT MUST BE COMPLETED BETWEEN

August 4, 2025 and October 10, 2025

COSHOCTON COUNTY, OHIO

ASPHALT CONCRETE PAVEMENT SPECIFICATIONS

1.0 GENERAL

- A. In addition to all other specifications governing materials, workmanship and construction methods, the following specifications shall become part of this contract.
- B. These modifications are made to increase durability, compaction properties, enhance aesthetics and assure safety to the general public.
- C. Technicians in charge of Quality Control shall be knowledgeable of the specification requirements and a copy of the project specifications shall be available at all times in the plant lab and control house.

1.1 REFERENCE

All reference to the specification numbers, unless otherwise noted on the plans or modified herein shall be considered to be specification numbers or the respective section thereof of the Ohio Department of Transportation Construction and Material Specifications, 2023 Edition.

1.2 APPROVALS

At or before the preconstruction conference, the contractor shall submit the following for approval:

- A. A list of key project personnel (Project Engineer/Manager, Project Superintendent, etc.) with office and mobile phone numbers to be used by the Engineer.
- B. A list of the paving equipment that will be used on this project (self-propelled paver, roller, distributor, etc.)
- C. Proposed materials and suppliers.
- D. Aggregate producer's ODOT prequalification information.
- E. A list of subcontractors and key personnel representing each.
- F. Proposed Job Mix Formulas (submitted in ODOT format).
- G. Current Asphalt Plant Calibration and Plant Quality Control Plan.

H. The Engineer or a representative appointed by the Engineer will respond to the items submitted within two (2) weeks. If an item is not approved, the contractor will have two (2) weeks from the time of notification to resubmit; allowing two (2) weeks after resubmitting for approval. No mix will be produced until approval is granted.

1.3 AGGREGATES

- A. The coarse fraction of asphalt concrete shall be limestone or "crushed" gravel for all courses. If crushed gravel is used for intermediate and base courses, the material will meet the requirements of ODOT 703.05 for Micro-Deval.
- B. Manufactured sand shall not be allowed in mixes containing reclaimed asphalt (RAP).
- C. Manufactured sand shall be limited to 10% maximum of the total mix for virgin mixes.
- D. Aggregate stockpiles will be identified and stocked in a manner to minimize segregation and commingling of materials.
- E. The loader bucket shall be at a height of 1' to 2' above the bottom of the stockpile or at a height that will not allow contamination or debris in the loaded aggregate.
- F. Aggregate shall be placed in the cold feed bins to the extent that it will not overflow into the adjacent bin/s.

1.4 ASPHALT BINDER

- A. The mix producer will furnish performance grade PG64-22, ODOT Item 702.01, for all courses.
- B. The Engineer may require a PG70-22(SBS) or 76-22 (SBS) virgin surface course for areas where heavy traffic or previous rutting have occurred. In those instances, the modified grade will be noted on the plans. The design would be a 50 blow Marshall Mix at the minimum cement content noted in these specifications, but the aforementioned modified binder would be substituted for the PG64-22.

1.5 ITEM 301 BITUMINOUS AGGREGATE BASE

- A. A maximum of 25% reclaimed asphalt may be used.
- B. The mix shall be a blend of limestone or "crushed" gravel coarse aggregates and natural sand.
- C. No manufactured sand will be allowed in mixes containing reclaimed asphalt.
- D. 10% manufactured sand may be used in virgin mixes only.
- E. The percent passing the No. 4 sieve shall be 44-52%.
- F. The minimum asphalt cement content shall be 5.5% by total weight of the mix.
- G. The fines to asphalt ratio shall not exceed 1.0.

*Except as modified herein the mix shall meet all other requirements of 441.02-1.

*The contractor shall design and produce the mix within the specification limits in Item E. No tolerance outside of the specification will be allowed. If production falls outside the specification limits the contractor will investigate and make the appropriate adjustments. If the contractor fails to bring the mix in tolerance within two tests production will cease until the problem is corrected.

1.6 441 TYPE 1 MODIFIED SURFACE

- A. A maximum of 10% reclaimed asphalt shall be allowed for this item.
- B. The mix shall be a blend of limestone or "crushed gravel" and natural sand.
- C. The use of aggregates where the bulk of the material is retained on the No. 8 sieve shall not be allowed for use in the mixes. This would include No. 9, No.10 or any size with a similar gradation.
- D. 10% maximum manufactured sand may be used.
- E. The percentage passing the No. 4 sieve shall be 58-65%.
- F. The minimum asphalt cement content shall be 6.6% by total weight of the mix.
- G. Acceptance voids shall be 2.0-3.5%. Voids higher than 3.5% when tested in the field will require an increase in cement until the target of 3.5% or less is metconsistently.
- H. The asphalt absorption and effective asphalt cement content shall be submitted with the proposed Marshall Mix Design.
- I. The fines to asphalt ratio shall not exceed 1.0.
- J. Marshall specimens to determine air voids shall be compacted at 275 +/-5 degrees Fahrenheit for design and production.

*The contractor shall design and produce the mix within the specification limits in Item D. No tolerance outside of the specification will be allowed. If production falls outside the specification limits the contractor will investigate and make the appropriate adjustments. If the contractor fails to bring the mix in tolerance within two tests production will cease until the problem is corrected.

^{*}Except as modified herein the mix shall meet all other requirements of 441.02-1.

1.7 441 TYPE 1 MODIFIED INTERMEDIATE COURSE

- A. A maximum of 15% reclaimed asphalt is allowed for this item.
- B. The mix shall be a blend of limestone or "crushed" gravel coarse aggregate and natural sand.
- C. The use of aggregates where the bulk of the material is retained on the No. 8 sieve shall not be allowed for use in the mixes. This would include No. 9, No.10 or any size with a similar gradation.
- D. No manufactured sand will be allowed in mixes containing reclaimed asphalt.
- E. 10% manufactured sand may be used in virgin mixes.
- F. The percentage passing the No. 4 sieve shall be 60-68%.
- G. The minimum asphalt cement content shall be 6.4% by total weight of the mix.
- H. Acceptance voids shall be 2.0-3.5%. Voids higher than 3.5% when tested in the field will require an increase in cement until the target of 3.5% or less is met consistently.
- The asphalt absorption and effective asphalt cement shall be submitted with the proposed Marshall Mix Design.
- J. The fines to asphalt ratio shall not exceed 1.0.
- K. Marshall specimens to determine air voids shall be compacted at 275 +/-5 degrees
 Fahrenheit for design and production.

*The contractor shall design and produce the mix within the specification limits in Item E. No tolerance outside of the specification will be allowed. If production falls outside the specification limits the contractor will investigate and make the appropriate adjustments. If the contractor fails to bring the mix in tolerance within two tests production will cease until the problem is corrected.

1.8 441 TYPE 2 MODIFIED INTERMEDIATE COURSE

- A. A maximum of 15% reclaimed asphalt is allowed for this item.
- B. The mix shall be a blend of limestone or crushed gravel and natural sand

^{*}Except as modified herein the mix shall meet all other requirements of 441.02-1.

Coshocton County, Ohio Revised February 20, 2025

- C. The use of aggregates where the bulk of the material is retained on the No. 8 sieve shall not be allowed for use in the mixes. This would include No. 9, No.10 or any size with a similar gradation.
- D. No manufactured sand will be allowed in mixes containing reclaimed asphalt
- E. 10% manufactured sand may be used in virgin mixes only.
- F. The percentage passing the No. 4 sieve shall be 45-53%.
- G. The minimum asphalt cement content shall be 5.5% by total weight of the mix.
- H. Acceptance voids shall be 2.0-3.5%. Voids higher than 3.5% when tested in the field will require an increase in cement until the target of 3.5% or less is met consistently.
- The asphalt absorption and effective asphalt cement shall be submitted with the proposed Marshall Mix Design.
- J. The fines to asphalt ratio shall not exceed 1.0.
- K. Marshall specimens to determine air voids shall be compacted at 275 +/-5 degrees
 Fahrenheit for design and production.

*The contractor shall design and produce the mix within the specification limits in Item D. No tolerance outside of the specification will be allowed. If production falls outside the specification limits the contractor will investigate and make the appropriate adjustments. If the contractor fails to bring the mix in tolerance within two tests production will cease until the problem is corrected.

1.9 RECLAIMED ASPHALT

Reclaimed asphalt proposed for use shall be identified as to source and stockpile location. Processed yard rap will not be allowed unless proper, recent testing has been completed on the identified source and stockpile. Laboratory test data shall be submitted to the Engineer as requested. The cost of the inspection and testing will be borne by the contractor and/or mix supplier.

A. A minimum of three (3) tests for asphalt cement content and gradation must be done, with the average used in the Job Mix Formula for gradation and cement content. Test data must be current and include one absolute viscosity.

^{*}Except as modified herein the mix shall meet all other requirements of 441.02-1.

- B. Reclaimed asphalt oxidized to the extent that an absolute viscosity cannot be obtained will not be allowed for use.
- C. Stockpiles will be free of debris and shall not be incorporated into the mix until the stockpile/s has been approved by the Engineer and/or his representative.
- D. The reclaimed asphalt shall be crushed and/or screened prior to mixing to minimize oversized.

 The screen shall be a minimum of 1 ½" for 301 Item, 1" for Type 2 Item and ½" for Type 1

 Intermediate.
- E. Failure to incorporate reclaimed into the mix in a manner satisfactory to the Engineer and/or his representative may result in the material being disallowed for use in future production as well as load rejection until corrections are made.

2.0 WORKMANSHIP

In addition to all other specifications governing workmanship and construction method as detailed in 401.08 the following specifications will become part of this contract.

- A. "Folding" of the hopper wings must be minimized and done only when necessary. Material that forms in the corners of the hopper shall be manually thoroughly scraped through an established protocol by the contractor to ensure the safety of the person(s) tasked with the scraping of the hopper. Scraping of this material shall be done often enough to ensure that the temperature of the material in the hopper corners does not cool to the extent that the material does not move freely through the hopper to the augers. The paver hopper should have enough material that the scrapings will mix well through the augers. Material should be at least at a quantity to the flow gates that they are full.
- B. The slat conveyor shall not be visible when the sides of the hopper are cleaned, or become visible during the paving process. Ensure adequate material in the paver hopper at all times during mix placement.
- C. Obvious end load segregation due to failure to implement proper workmanship shall result in a 90% pay factor applied to the days production based on the unit bid price.
- D. Place asphalt concrete only if the surface is dry and weather conditions permit proper handling, finishing and compaction. In addition to Table 401.05-1 for minimum temperatures, surface and air temperatures must be 50 degrees F (10 C) and rising for all surface mixes regardless of the thickness.

- E. The presence of extraneous material, primarily dust balls from the plant in the mix shall be cause to immediately cease production until corrective action can be taken.
- F. Finished surfaces shall be smooth to a tolerance of 1/4" in 10 Feet.

3.0 PLANT PRODUCTION

- A. Computer data: The plant computer shall be operational at all times. Should a printer problem or other technical difficulties arise, the problem shall be corrected immediately. The plant operator will inform the Engineer and/or the Engineers contracted laboratory of any computer malfunctions and what corrective action has to be taken. Should the problem not be corrected in a timely manner, production will cease.
- B. Throughout production, the computer printouts shall be reviewed and at the end of each day's production the computer printouts, as requested shall be provided to the Engineers contracted laboratory to be reviewed by the Engineers Quality Assurance Representative.
- C. The switching of mixes while in production from mixes with coarse aggregate (larger than ½") to surface course shall not be allowed.
- D. The presence of extraneous material, primarily dust balls from the plant in the mix shall be cause to immediately cease production until corrective action is taken.
- E. Mix quantities in the silo shall be kept to a level to minimize segregation. Silo configuration, batcher capacity and timing will determine this quantity.
- F. Trucks shall be loaded in three (3) drops to minimize segregation. The rear, front and then the middle shall be loaded as recommended by the asphalt institute.
- G. Mix temperatures shall not vary by more than 20 degrees Fahrenheit from one truck to another.
- H. The following shall be production temperature ranges and are dependent on air temperatures, wind velocities and distance to the placement.

MIX TYPE	MINIMUM TEMPERATURE	MAXIMUM TEMPERATURE
Type 1 Surface	290 degrees Fahrenheit	325 degrees Fahrenheit
Type 1 Intermediate	310 degrees Fahrenheit	325 degrees Fahrenheit
Type 2/301	280 degrees Fahrenheit	325 degrees Fahrenheit

^{*} Mixes containing modifiers will be in accordance with manufacturer's recommendations.

Mixes produced with modified cements shall be a minimum of 300 degrees F at the paver.

- *Temperatures exceeding 325 F will not be rejected, but notification will be given to the plant to bring the temperature within range. Mix exceeding 350 will be rejected. If the mix is not brought within range within two trucks production will cease until the cause is identified and corrected.
- Truck beds shall be clean and sprayed with a uniform coating of release agent,
 Excess release agent and puddling in the beds will not be acceptable. The release agent shall be operational at all times; with any water dilutions within the manfacturer's recommendations.
- J. <u>DIESEL FUEL IN TRUCK BEDS IS NOT ALLOWED.</u> The plant operator shall monitor truck bed preparation. Trucks that do not comply should be put on notice.
- K. Changes in bin percentages to bring the mix into conformity with the JMF shall be documented on the TE-199 under mix proportions.
- Aggregate and reclaimed moisture contents entered into the computer shall be
 from current laboratory testing and adjusted only as moisture conditions change.
 Adjustments to the computer moisture entries will not be allowed without test
 verification.
- M. When producing mixes that include reclaimed asphalt, production rates (TPH) will be set at a rate that will produce a sufficient blending of the reclaimed and virgin aggregates.
- N. The asphalt cement specific gravity from the transport tickets shall be entered in the computer and adjusted only as transport tickets dictate.

5.0 QUALITY ASSURANCE REPRESENTATIVE

The Engineer may employ an independent testing laboratory to perform periodic mix testing, compaction testing, plant inspection and any other testing or inspection required to ensure materials, methods and processes are suitable and meet project specifications. The Engineer will coordinate with the contractor or material supplier a minimum of 24-hours in advance.

6.0 PROCEDURES FOR OPERATIONS

- A. All work associated with this contract shall be performed between 7:00 A.M and 7:00 P.M. Monday through Friday.
- B. Notice of Saturday work shall require a minimum of 24 hours' notice (on a week by week basis) and must be approved by the Engineer.
- C. If conditions are acceptable, daily work hours maybe be extended with approval from the Engineer.
- D. No work will be permitted on Sunday without written permission from the Engineer.
- E. No work will be permitted on legal public holidays.
- F. The contractor shall notify the Engineer 48 hours prior to the start of operations.
- G. Weather requirements are as outlined in Item 2.0 (D.)
- H. If the contractor suspends operations on this contract for more than 3 working days (excluding holidays and weekends) the contractor shall notify the Engineer 48 hours prior to resuming operations. The contractor may make rescheduling arrangements with the Engineer prior to suspending work, but the contractor will be responsible for notifying the Engineer of any changes to any established arrangements.
- These requirements are to be followed by the general contractor and any sub- contractor on this
 project.
- J. Damage to areas outside of the designated work limits as a result of the contractor, subcontractor or duly appointed agent's operations shall be repaired at the contractor's expense.
- K. Excavated areas will be secured prior to the end of each working day and will have adequate protection until such time the area/s no longer pose a risk to the public.
- L. Stockpiling of materials overnight on the job site will not be permitted.
- M. Streets and/or roadways with base conditions that are disturbed due to heavy loads shall have decreased tonnages on trucks as not to cause additional damage.

8.0 ROADWAY PROPERTIES

- A. Pavement width shown on the plans is approximate.
- B. The pavement shall be resurfaced to its full width or to a width determined by the Engineer in the field.
- C. The Engineer and the contractor shall inspect the road prior to beginning the resurfacing operation, to determine the width to be paved, if plan notes do not indicate a pavement width, the contractor shall match the width of the existing pavement.
- D. If the contractor's operation is unable to produce an accurate and consistent edge; the contractor may be directed by the Engineer to use a string line when placing asphalt courses.

9.0 PRE-LEVELING

- A. When specified in the plans, the contractor shall place an intermediate course of asphalt concrete on the roadway to correct any depressions, settlements, longitudinal or crown deficiencies in the existing pavement.
- B. The asphalt shall be placed in variable widths and depths as directed by the Engineer's representative in the field, or as depicted within the project plans.
- C. The contractor may also be required to place pre-leveling to maintain or modify the rate of super elevation or to a slope as directed by the Engineer.

10.0 FEATHERING

- A. At points where the proposed work begins or ends at intersections, the final asphalt course shall be feathered to meet the existing roadway surface.
- B. On roads to be resurfaced and on adjacent side roads the ratio of this feathering shall be 1" per 12 feet and shall be contained within the limits of work described in the plans or as directed by the Engineer.

11.0 JOINTS

A. Open longitudinal joints shall not be permitted; however, when a cold joint is unavoidable, its vertical face shall be uniformly coated with ODOT Item 407 Tack Coat similar to that specified for intermediate and surface asphalt courses. All costs related to performing this work shall be included in the unit price bid for all courses.

12.0 SEALING FEATHERS AND BUTT JOINTS

- A. A well bonded and sealed joint is required
- B. Where the asphalt surface required to be feathered to meet an adjoining surface, including private driveways, the completed feathered surface and adjacent existing surface shall be coated with a thin coat of rubberized crack sealant approximately 8" in width.
- C. Traffic shall not be permitted on the sealed joint until the asphalt cement has cooled sufficiently to prevent tracking.
- D. The bituminous material used and the cost of sealing joints as described above shall be included in the unit price bid for surface course items.

13.0 DRIVEWAYS

- A. Butt joints 18" wide shall be cut for asphalt driveways to ensure a smooth transition from the roadway surface. Butt joints shall be feathered to a maximum of 4' from the edge of pavement or as directed by the Engineer. All concrete driveways will be reviewed by the Contractor and Engineer.
- B. Aggregate driveways shall be wedged with crushed aggregate immediately following the asphalt paving operation to maintain adequate access.

14.0 MAILBOX APPROACHES

- A. Mailbox approaches shall be constructed of their respective materials based upon existing conditions and or as directed by the Engineer.
- B. Sufficient quantities of required material have been included in the general summary for this work.
- C. The approaches shall be constructed in such a manner as to maintain proper cross slope and elevation with the adjacent pavement and berm.

15.0 BERMS

Where RAP is specified to be used for berm reconditioning and paved berm back-up, the work shall follow as closely as possible behind the paving operations and the length of the unconditioned shoulder shall be held to a minimum.

- A. All shoulder reconditioning shall be completed no later than five (5) calendar days after the placement of the surface course unless otherwise approved by the Engineer.
- B. All berm compaction shall be completed with a pneumatic tired roller.
- C. Proper cross slope (1/2" per foot) and proper elevations of the stabilized aggregate berm shall be achieved upon completion of compaction.
- D. At no time will the compacted berm be permitted to be higher than the adjacent pavement.
- E. The contractor will not have any liability to maintain berm after it has been accepted by the Engineer.
- F. After this acceptance the county will assume responsibility for maintenance of the berm

16.0 ROLLERS

- A. Rollers shall be only of the steel wheel type and pneumatic tire types meeting the minimum requirements of section 401.03 of the specifications.
- B. The use of a pneumatic tire roller is required for all leveling courses.
- C. When the tonnage production per hour and the area of coverage requires the use of three (3) rollers, the rollers will be in a sequence that assures adequate compaction and good aesthetics. Any change in rollers required must be approved by the Engineer prior to the day's production. The tonnage requirements and square yards covered shall govern, regardless of field density requirements under ODOT Supplemental 1055.

- D. Rollers shall be operational at all times. Should a roller break down, the placement will be slowed to a lesser tonnage for the number of rollers remaining until repairs are made.
- E. Vibration shall not be used on courses less than 1 ½" or where there are underlying unstable conditions, utilities or residences which may be disturbed. In most instances the vibratory roller will not be allowed in the vibratory mode.

17.0 PAVEMENT REPAIR

- A. The area to be repaired will be designated by the Engineer prior to the start of work.
- B. The existing pavement shall be saw cut at these limits (unless a milling head is used) and removed. The contractor shall take care to prevent disturbing or undermining the abutting pavement.
- C. After the existing pavement has been removed, the contractor and the Engineer shall inspect the sub grade. If the sub grade is found to be unsuitable, it shall be removed to a depth determined by the Engineer and backfilled with Item 301 and compacted. All removal shall in accordance with Item 202 and disposed of accordingly.
- D. Payment for this item shall include all labor, materials, equipment and incidentals required to remove and dispose of unsuitable sub grade.
- E. Prior to placing any bituminous base, all vertical faces shall be cleaned and coated with bituminous material in accordance with section 401.06.
- F. The asphalt shall be placed in a minimum of two (2) equal lifts (unless otherwise approved by the Engineer) with each lift compacted thoroughly.
- G. The final lift shall be finished flush with the existing pavement surface. This area shall be maintained flush by the contractor until the pavement is resurfaced.
- H. Where resurfacing is not specified in the repair area, the finish course shall be 441 Type 1 for a compacted thickness of 1 ½".
- I. The edges of all pavement repairs shall be sealed with a rubberized crack sealant if the plans do not include an asphalt overlay as part of the plans.
- J. Payment for this item will be at the unit bid for item 253 pavement repairs as perplan.

18.0 PAVEMENT PLANING, ASPHALT CONCRETE

- A. This work shall conform to Item 254 Pavement Planing with the following exceptions:
 - 1. The areas calling for pavement planing are approximate.
 - The contractor and Engineer shall inspect all locations for planing to determine the depth and area of the wearing course to be removed as well as the equipment requirements based on the environmental surroundings.
 - All planed areas shall be paved within two (2) working days except as directed or permitted by the Engineer.
- B. All vertical edges shall be ramped with cold mix or hot mix asphalt placed on burlap, or as directed by the Engineer to provide a smooth and safe transition from the planed surface to the existing pavement. This shall be at a minimum slope of 12.1 or in some cases to provide driveway access.
- C. Butt joints shall be constructed as shown on ODOT Standard Drawing BP- 3.1 or as directed by the Engineer.
- D. At some locations, the contractor will be planing an entire roadway section or lane width. This planing will be at a range depth of 0" to 3" or greater. Proper cross slope is to be established during planing.
- E. Planed material shall become the property of the Coshocton County Engineer's Office and disposed of at designated locations as directed by the Engineer. Payment for disposal of planing material shall be included in Item 254 Planing Grindings Hauled, As Per Plan.
- F. Payment for this item shall include all labor, equipment, material, removed and transfer of material and any incidentals required to perform the stated work.
- G. Payment will be at the unit bid price for Item 254.

19.0 ITEM 407 - TACK COAT

This work shall conform to ODOT Item 407-Tack Coat with the following exceptions:

- A. The contractor shall not apply tack coat more than 1,500 feet ahead of the paving operation or more area than can be covered with asphalt by the end of the workday. If surface course is placed over an intermediate course within 24 hours and the surface temperature exceeds 70 degrees Fahrenheit the application of tack may be waived by the Engineer when the area has not been open to traffic and the surface is clean and free of debris.
- B. Should the intermediate or leveling course be open to traffic for more than 24 hours and the surface has become dirty or contaminated, the contractor will be required to clean and tack the intermediate or leveling course.
- C. This work shall be performed at no additional cost to the Engineer or other agency covered under these specifications.
- D. Payment for this item shall include labor, materials, equipment, incidentals and required cleaning and/or cover aggregate if necessary.
- E. Payment will be at the unit bid price for Item 407 Tack Coat.

20.0 PUBLIC SAFETY AND TRAFFIC MAINTNENANCE

- A. The contractor shall provide and maintain lights, signs and barricades for the protection of the work and the safety and convenience of the traveling public.
- B. The contractor shall be responsible to provide traffic control devices for operations as described in the current edition of the Ohio Manual of Uniform Traffic Control Devices (OMUTCD).
- C. The contractor, subcontractor or duly appointed agent shall notify Engineer prior to any permanent traffic striping.